

FIXTURE TYPE	
MODEL NUMBER	
PROJECT	

CEW Series Architectural Emergency Lighting

SPECIFICATIONS

ILLUMINATION

- Universal 120/277-volt 60 Hz input - other voltages available upon request.
- Minimum of 90 minutes of emergency illumination.
- Supplied with two MR16 LED heads.

ELECTRICAL

- Fully automatic solid-state charger returns battery to full charge according to UL guidelines.
- Solid state relay supervision.
- Low battery voltage disconnect.
- AC lockout.
- Brownout protection.
- High-charge LED indicator.
- Test switch.
- Long-life, maintenance-free, valve-regulated lead-acid battery.

MOUNTING

- It can be wall or ceiling mounted.

HOUSING

- UV stable, high impact, injection molded, V-O flame resistant housing.
- Attractive contemporary design.
- Compact, low profile.

OPTIONS

- Self-Test/Self-Diagnostics.
- Cord and Plug (120 VAC).
- Nickel Cadmium Battery (16 and 27 watts only).
- Damp Rating.

WARRANTY / LISTING

- One-year warranty from the date of shipment on the entire unit. The battery will carry an additional pro-rata warranty. See Warranty Statement for details.

AGENCY APPROVALS

- ETL Listed to UL924. Meets or exceeds the requirements of the National Electrical Code and NFPA 101.
- BAA/ARRA/TAA/BABA

DIMENSIONS

- 12³/₄"L x 5"H x 5¹/₂"W



ORDERING INFORMATION

SAMPLE PART

CEW-6-11-LED-W-E

Voltage

- **6** - 6 Volt
- **12** - 12 Volt

Capacity

- **11** -11 Watts
- **16**- 16 Watts ³
- **18**-18 Watts
- **27**-27 Watts
- **32**-32 Watts
- **40**-40 Watts ¹

Lamps

- **X**- 5 watts
- **Y**-10 Watts
- **Z**- 12 Watts
- **T**-20 Watts ²
- **LED**-14 Watts

Housing Color

- **W** -White
- **B** -Black

Options

- **E** Self-Diagnostic
- **CP** Cord and Plug (120VAC)
- **NI** Nickel Cadmium Battery (16 and 27 watts only)
- **DR** Damp Rating

NOTES

- ¹ 12-volt unit, 40-watt equivalent. 32 watts capacity.
- ² 20-Watt light output equivalent to a 16-watt lamp.
- ³ NICAD Models only.