



Spin Free

Pocket-sized
EV charger

3 kW AC



POWER

CHARGE

FAULT

Take total control of your charging

The Spin Free 3kW Portable charger – a rugged, portable EV charger crafted for India's homes and roads. Small enough to fit your trunk, tough enough for monsoons and heat, it keeps your ride charged, wherever life takes you.



Zero Setup, Instant Charging

No app, No wifi? No worries, just plug in and charge. It's as easy as it gets.



Weather Ready, Wherever You Are

IP67 Outdoor rating. Built to handle rain heat and dust so you can charge confidently no matter the weather.

Everything you might be asking for

- + Eco-certified materials
- + High voltage surge capability
- + Visual status Indicator LEDs
- + Compatible with all EV cars
- + BIS certified (IS17120) with safety RCD
- + Weatherproof IP67 rating. Built for India's toughest days
- + Global appeal, local fit with universal compatibility
- + 3kW fast charging – getting you ready for the road
- + Type M inlet plug temperature sensing and protection
- + Wide temperature range – up to 55°C
- + High quality cable and type 2 charging plug
- + Protection with leakage current

Specification

Power Output

Charging Power: 3.0 kW
AC Output: 165 – 275 VAC
Connection point: IEC 62196-2 Type-2
Mode of Charging: Mode-2
Max. AC Output Current: 13 A (16A as special option)
Number of Plug: 1

Mains Input

Input Voltage Range: 165 to 275 VAC
AC Input Plug: India type M (16A)
AC Power Rating (max): 13 A, 3.0 kVA@ 230 Vac
Input Frequency Range: 45 – 63 Hz

Protection and Safety

Safety Alarms: Over Current, Over Voltage, Under Voltage, Residual Current, Surge Protection, Over Temperature (charging unit and inlet plug), Short Circuit, Weld Detection
Residual Current: RCMU type B (30mA AC + 6mA DC)
Insulation Resistance: IR > 10Mohm
LED Indications: Power, Charging, Fault
Compliant with IS 17120 (reference IEC 62752)

User Interface and Comms

EVSE and EVCC: IEC 61851-1 Annexure A

Mechanical

Ingress Protection: IP 67
Dimension (H*W*D): 260 * 73 * 59 mm
Charging Cable Length: 5m
Material: Polycarbonate + ABS (UL94-V0)
Mounting: Portable
Cooling: Natural Air

Environmental

Operating Temperature: -30 to 50 degC (extended range up to 50 degC)
Storage Temperature: -40°C to 75°C
Altitude: 4,000 meters
Humidity (Non-Condensing): 5 % to 95 %

THIS DOCUMENT CONTAINS INFORMATION THAT IS SUBJECT TO CHANGE WITHOUT NOTICE.

No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including, but not limited to, copying, recording, retrieving data, or computer networks without the written permission of Exicom. Exicom and all other Exicom product names and slogans are trademarks or registered trademarks of Exicom. Exicom products can be protected by one or more patents.

All other products and services mentioned may be trademarks or service marks of their respective owners. Illustrations of the product and user interface are exemplary and may differ from the actual appearance.

February 2026 – Version 1

© 2026 by Exicom.

All rights reserved



EV chargers for homes and businesses

Exicom is distributed and maintained by a network of qualified partners and resellers. Find more information and your local partner at:

[exicom.com](https://www.exicom.com)







Scan for

Digital Brochure

 **exicom** | beautifully engineered™