

HIGH DEFINITION ACCESSORIES | BNC ADAPTOR



OVERVIEW - Designed to meet the requirements of High Definition up to SMPTE 424M (HDTV) and Serial Digital (SDV) but also suitable for Analogue television, this adaptor is a useful addition to the high definition range.

Plugging straight into the front of a MUDigSA style video panel, these provide a convenient way of using a standard 75 ohm BNC cable with the panel.



Product Code	Description
ADAPT04-HDBNC	HD Plug - BNC Socket Adaptor

To obtain a quote:

Call: +44 (0)1724 273224
Email: sales@dem-uk.com

TECHNICAL SPECIFICATION

DC to 3GHz

Contact Resistance	Inner Conductor $\leq 5\text{m}\Omega$ Outer Conductor $\leq 3\text{m}\Omega$
Insulation Resistance	$\geq 10\text{G}\Omega$
Voltage Proof	1KVeff/50Hz
Impedance (BNC)	75 Ω
Return Loss	$>20\text{dB}/3\text{GHz}+$ $\leq 0.3\text{dB}/3\text{GHz}$
Mating Cycles	≥ 2500
Force to Engage	Straight Plug 10 N
Thermal and Climatic Characteristics (According to DIN IEC 68-1 40/155/21)	Storage and Operating Temperature -40C up to $+65\text{C}$ Moisture resistance according to MIL Spec. 202

