


RES10-M General Purpose EMI Filters

Medical Applications

Roxburgh EMC's RES10-M range are single phase filters, designed specifically for the medical industry. They offer a general purpose filtering performance with eight versions to select from and an operating frequency from dc to 400Hz.

Temperature Derating Curve for EMC Filters Rated at 40°C Ambient and 100°C Maximum



Call us on:

Tel: +44 (0) 1724 273228

Features:

- 1 Amp to 30 Amp Options
- Single Phase
- General Purpose Filtering Performance
- UL Approved E191581

Benefits:

- Compact size for rated current
- Fast-on, screw or wire terminations
- Quick and Easy Mounting
- Available from UK Stock

Applications:

These filters are designed for applications within the **medical industry**.

Full technical specification on page 2

Other options in this range on page 3

DEM Manufacturing

Deltron Emcon House
Hargreaves Way
Sawcliffe Industrial Park
Scunthorpe, North Lincolnshire.
DN15 8RF

ROXBURGH EMC




Tel: +44 (0) 1724 273200

Email: sales@dem-uk.com

Web: www.dem-uk.com/roxburgh


Circuit diagram:



Electrical parameters:

Rated Voltage:	120/250VAC
Rated Current at an ambient temp:	6A@40°C
Operating Frequency:	50/60Hz
Climatic Class(IEC60068-1):	25/100/21
Operational Leakage current: (at 250VAC/50Hz and Total C +/-20%)	0.8mA max (RES10F06-M 0mA)
Operational Leakage current: (at 120VAC/60Hz and Total C +/-20%)	0.46mA max (RES10F06-M 0mA)
Test Voltage(100%)for 2 sec:	
	L-N: 1100VDC/20mA
	L/N-PE: 2250VDC/20mA

Dimensions(mm):



Filter parameters:

Total Inductance(L-L'/N-N'):	1mH +50%,-35%
Total Capacitance(L-N/L'-N'):	0.1uF +/-20%
Total Capacitance(L/N-PE) (RES10F06-M):	9.4nF +/-20% (0nF)
Total Resistance(L-N/L'-N'):	1M Ω +/-10%
Weight(Approximate):	55g

Safety certification

UL	☒	CSA	☒
ENEC	☒	CQC	☐
CE	☒	VDE	☐

Technical Specification

compiled by	Jay Zhang	2020-8-5
reviewed by	Pallas Wang	2020-8-5
approved by	Henry Huang	2020-8-5



ROXBURGH *EMC*  +44 (0)1724 273200
sales@dem-uk.com
www.dem-uk.com/roxburgh

ROXBURGH *EMC*  +44 (0)1724 273200
sales@dem-uk.com
www.dem-uk.com/roxburgh

Part **RES10F06**
 Number (Alternate RES10F06-M - no Y caps)

Part **RES10F06**
 Number (Alternate RES10F06-M - no Y caps)

single-phase emc filter	
stage marker	V1.03

single-phase emc filter	
stage marker	V1.03

RES10-M General Purpose EMI Filter

Medical Applications

Options Available:

Part Number	Rated Current @40°C A	Leakage Current @ 230V/50Hz mA	Inductance ΣL mH	Capacitance ΣCx uF	Resistance ΣR K Ω	Connection Type		
								
RES10F01-M	1	0.002	12	0.1	1000	F	W	
RES10F03-M	3	0.002	2.5	0.1	1000	F	W	
RES10F06-M	6	0.002	1.0	0.1	1000	F	W	
RES10F10-M	10	0.002	0.8	0.1	1000	F	W	
RES10F12-M	12	0.002	0.7	0.1	1000	F	W	
RES10F16-M	16	0.002	0.7	0.1	1000	F	W	
RES10F20-M	20	0.002	0.6	0.1	1000	F	W	
RES10S30-M	30	0.002	0.7	0.47	1000			S

Call us on:

+44 (0) 1724 273200



DEM Manufacturing

Deltron Emcon House, Hargreaves Way, Sawcliffe Industrial Park,
Scunthorpe, North Lincolnshire, DN15 8RF

Tel: +44 (0) 1724 273200

Email: sales@dem-uk.com

Web: www.dem-uk.com/roxburgh