


RES10-M General Purpose EMI Filters

Medical Applications

Roxburgh EMC's RES10-M range are single phase filters, designed specifically for the medical industry. They offer a general purpose filtering performance with eight versions to select from and an operating frequency from dc to 400Hz.

Temperature Derating Curve for EMC Filters Rated at 40°C Ambient and 100°C Maximum



Call us on:

+44 (0) 1724 273228

Features:

- 1 Amp to 30 Amp Options
- Single Phase
- General Purpose Filtering Performance
- UL Approved E191581

Benefits:

- Compact size for rated current
- Fast-on, screw or wire terminations
- Quick and Easy Mounting
- Available from UK Stock

Applications:

These filters are designed for applications within the **medical industry**.

Full technical specification on page 2

Performance curves on page 3

Other options in this range on page 4

DEM Manufacturing

Deltron Emcon House
Hargreaves Way
Sawcliffe Industrial Park
Scunthorpe, North Lincolnshire.
DN15 8RF



ROXBURGH EMC



Tel: +44 (0) 1724 273200

Email: sales@dem-uk.com


Web: www.dem-uk.com/roxburgh

Circuit diagram:			Dimensions(mm):			
						
Electrical parameters:						
Rated Voltage:		120/250VAC				
Rated Current at an ambient temp:		16A@40°C				
Operating Frequency:		50/60Hz				
Climatic Class(IEC60068-1):		25/100/21				
Operational Leakage current: (at 250VAC/50Hz and Total C +/-20%)		0.8mA max (RES10F16-M 0mA)				
Operational Leakage current: (at 120VAC/60Hz and Total C +/-20%)		0.46mA max (RES10F16-M 0mA)				
Test Voltage(100%)for 2 sec:						
L-N:		1100VDC/20mA				
L/N-PE:		2250VDC/20mA				
Filter parameters:						
Total Inductance(L-L'/N-N'):			0.7mH +50%,-35%			
Total Capacitance(L-N/L'-N'):			0.1uF +/-20%			
Total Capacitance(L/N-PE) (RES10F16-M):			9.4nF +/-20% (0nF)			
Total Resistance(L-N/L'-N'):			1MΩ +/-10%			
Weight(Approximate):			120g			
Safety certification			Technical Specification			
UL	☒	CSA	☒	compiled by	Jay Zhang	2020-8-5
ENEC	☒	CQC	☐	reviewed by	Pallas Wang	2020-8-5
CE	☒	VDE	☐	approved by	Henry Huang	2020-8-5
Part RES10F16			single-phase emc filter			
Number (Alternate RES10F16-M - no Y caps)			stage marker V1.03			
						
+44 (0)1724 273200 sales@dem-uk.com www.dem-uk.com/roxburgh						


ROXBURGH EMC

FILTER INSERTION LOSS CHARACTERISTICS CISPR 17 - 50 OHM METHOD

RES10F16-M



COMMON MODE



DIFFERENTIAL MODE



RES10-M General Purpose EMI Filter

Medical Applications

Options Available:

Part Number	Rated Current @40°C A	Leakage Current @ 230V/50Hz mA	Inductance ΣL mH	Capacitance ΣCx uF	Resistance ΣR K Ω	Connection Type		
								
RES10F01-M	1	0.002	12	0.1	1000	F	W	
RES10F03-M	3	0.002	2.5	0.1	1000	F	W	
RES10F06-M	6	0.002	1.0	0.1	1000	F	W	
RES10F10-M	10	0.002	0.8	0.1	1000	F	W	
RES10F12-M	12	0.002	0.7	0.1	1000	F	W	
RES10F16-M	16	0.002	0.7	0.1	1000	F	W	
RES10F20-M	20	0.002	0.6	0.1	1000	F	W	
RES10S30-M	30	0.002	0.7	0.47	1000			S

Call us on:

+44 (0) 1724 273200



DEM Manufacturing

Deltron Emcon House, Hargreaves Way, Sawcliffe Industrial Park,
Scunthorpe, North Lincolnshire, DN15 8RF

Tel: +44 (0) 1724 273200

Email: sales@dem-uk.com

Web: www.dem-uk.com/roxburgh