


RES30-M High Performance EMI Filter

Medical Applications

Roxburgh EMC's RES30-M range are single phase filters, designed specifically for the medical industry. They offer a high attenuation performance and are well suited for particularly noisy applications. There are ten variations to select from with an operating frequency from dc to 400Hz.

Temperature Derating Curve for EMC Filters Rated at 40°C Ambient and 100°C Maximum



Call us on:

+44 (0) 1724 273228

Features:

- Single Phase
- High Attenuation Performance
- 1 Amp to 30 Amp Options
- UL Approved E191581

Benefits:

- Compact size for rated current
- Fast-on, screw or wire terminations
- Quick and Easy Mounting

Applications:

These filters are designed for applications within the **medical industry**.

Full technical specification on page 2

Other options in this range on page 3

DEM Manufacturing

Deltron Emcon House
Hargreaves Way
Sawcliffe Industrial Park
Scunthorpe, North Lincolnshire.
DN15 8RF



ROXBURGH EMC



Tel: +44 (0) 1724 273200

Email: sales@dem-uk.com

Web: www.dem-uk.com/roxburgh

Circuit diagram:		Dimensions(mm):						
								
Electrical parameters:								
Rated Voltage:	120/250VAC	Filter parameters:						
Rated Current at an ambient temp:	6A@40°C							
Operating Frequency:	50/60Hz							
Climatic Class(IEC60068-1):	25/100/21							
Operational Leakage current: (at 250VAC/50Hz and Total C +/-20%)	0.8mA max (RES30F06-M 0mA)	Total Inductance(L-L'/N-N'):	8mH +50%,-35%					
Operational Leakage current: (at 120VAC/60Hz and Total C +/-20%)	0.46mA max (RES30F06-M 0mA)	Total Capacitance(L-N/L'-N'):	0.94uF +/-20%					
Test Voltage(100%)for 2 sec:	L-N:	Total Capacitance(L/N-PE) (RES30F06-M):	9.4nF +/-20% (0nF)					
	L/N-PE:	Total Resistance(L-N/L'-N'):	680KΩ +/-10%					
		Weight(Approximate):	110g					
		Safety certification						
		UL	☒	CSA	☒	Technical Specification		
		ENEC	☒	CQC	☐	compiled by	Jay Zhang	2020-8-5
		CE	☒	VDE	☐	reviewed by	Pallas Wang	2020-8-5
						approved by	Henry Huang	2020-8-5
  +44 (0)1724 273200 sales@dem-uk.com www.dem-uk.com/roxburgh		Part		RES30F06		single-phase emc filter		
		Number (Alternate RES30F06-M - no Y caps)				stage marker		V1.03

RES30-M High Performance EMI Filter

Medical Applications

Options Available:

Part Number	Rated Current @40°C A	Leakage Current @ 230V/50Hz mA	Inductance ΣL mH	Capacitance ΣCx uF	Resistance ΣR K Ω	Connection Type		
								
RES30F01-M	1	0.002	20	0.44	1000	F	W	
RES30F03-M	3	0.002	14	0.66	1000	F	W	
RES30F04-M	4	0.002	14	0.66	1000	F	W	
RES30F06-M	6	0.002	8	0.94	680	F	W	
RES30F08-M	8	0.002	8	0.94	680	F	W	
RES30F10-M	10	0.002	8	0.94	680	F	W	
RES30F12-M	12	0.002	4	2.00	330	F	W	
RES30F16-M	16	0.002	4	2.00	330	F	W	
RES30F20-M	20	0.002	4	2.00	330	F		S
RES30S30-M	30	0.002	2	2.00	330			S

Call us on:

+44 (0) 1724 273200



DEM Manufacturing

Deltron Emcon House, Hargreaves Way, Sawcliffe Industrial Park,
Scunthorpe, North Lincolnshire, DN15 8RF

Tel: +44 (0) 1724 273200

Email: sales@dem-uk.com

Web: www.dem-uk.com/roxburgh