


RES90-M Excellent Attenuation Performance

Medical Applications

Roxburgh EMC's RES90-M range are two-stage filters, designed specifically for the medical industry. This series offers excellent attenuation performance and are well suited for noisy applications requiring excellent filter performance. There are ten variations to select from with rated current between 1amp and 30amp.



Temperature Derating Curve for EMC Filters Rated at 40°C Ambient and 100°C Maximum



Call us on:

+44 (0) 1724 273228

Features:

- Two-Phase Filter
- Excellent Attenuation Performance
- UL Approved E191581
- For use from DC to 400Hz

Benefits:

- Compact size for rated current
- Fast-on, screw or wire terminations
- Quick and easy mounting

Applications:

These filters are designed for applications within the **medical industry**.

Full technical specification on page 2

Other options in this range on page 3

DEM Manufacturing

Deltron Emcon House
Hargreaves Way
Sawcliffe Industrial Park
Scunthorpe, North Lincolnshire.
DN15 8RF



ROXBURGH *EMC*



Tel: +44 (0) 1724 273200

Email: sales@dem-uk.com

Web: www.dem-uk.com/roxburgh

Circuit diagram:		Dimensions(mm):					
							
Electrical parameters:							
Rated Voltage:		120/250VAC					
Rated Current at an ambient temp:		10A@40°C					
Operating Frequency:		50/60Hz					
Climatic Class(IEC60068-1):		25/100/21					
Operational Leakage current: (at 250VAC/50Hz and Total C +/-20%)		0.73mA max (RES90F10-M 0mA)					
Operational Leakage current: (at 120VAC/60Hz and Total C +/-20%)		0.43mA max (RES90F10-M 0mA)					
Test Voltage(100%)for 2 sec:							
L-N:		1100VDC/20mA					
L/N-PE:		2250VDC/20mA					
Filter parameters:							
Total Inductance(L-L'/N-N'):				16mH +50%,-35%			
Total Capacitance(L-N/L'-N'):				1.41uF +/-20%			
Total Capacitance(L/N-PE) (RES90F10-M):				8.6nF +/-20% (0nF)			
Total Resistance(L-N/L'-N'):				330KΩ +/-10%			
Weight(Approximate):				465g			
Safety certification				Technical Specification			
UL	☒	CSA	☒	compiled by	Jay Zhang	2020-8-5	
ENEC	☒	CQC	☐	reviewed by	Pallas Wang	2020-8-5	
CE	☒	VDE	☐	approved by	Henry Huang	2020-8-5	
Part RES90F10				single-phase emc filter			
Number (Alternate RES90F10-M - no Y caps)				stage marker		V1.03	

ROXBURGH

EMC

+44 (0)1724 273200

sales@dem-uk.com

www.dem-uk.com/roxburgh

RES90-M Excellent Attenuation Performance

Medical Applications

Options Available:

Part Number	Rated Current @40°C A	Leakage Current @ 230V/50Hz mA	Inductance ΣL mH	Capacitance ΣCx uF	Resistance ΣR K Ω	Connection Type		
								
RES90F01-M	1	0.002	20	0.22	680	F	W	
RES90F03-M	3	0.002	14	0.33	470	F	W	
RES90F04-M	4	0.002	14	0.33	470	F	W	
RES90F06-M	6	0.002	8	0.47	330	F	W	
RES90F08-M	8	0.002	8	0.47	330	F	W	
RES90F10-M	10	0.002	8	0.47	330	F	W	
RES90F12-M	12	0.002	4	1	220	F	W	
RES90F16-M	16	0.002	4	1	220	F	W	
RES90F20-M	20	0.002	2.7	1	220	F		S
RES90S30-M	30	0.002	1.5	1	220			S

Call us on:

+44 (0) 1724 273200



DEM Manufacturing

Deltron Emcon House, Hargreaves Way, Sawcliffe Industrial Park,
Scunthorpe, North Lincolnshire, DN15 8RF

Tel: +44 (0) 1724 273200

Email: sales@dem-uk.com

Web: www.dem-uk.com/roxburgh