

1

2

3

4

5

6

7

PMF10

AKA

ALTITUDE

CURRENT

CLASS

DEVICE

EARTHING

ENCLOSURE

ENVIRONMENT

FLAMMABILITY

GND BOND

HUMIDITY

INSULATION

IP RATING

LOSS

LEAKAGE

MASS

MATERIAL

MOUNTING

MTBF

OVERLOAD

OVERVOLTAGE

PACKAGING

PCB

POLLUTION

POTTING

POWER

RESIDUAL

RESISTANCE

SCCR

SHOCK

SPACING

STYLE

SUPPLY

TERMINAL

VARISTOR

VIBRATION

VOLTAGE

WITHSTAND

EU/UK

US

CAN

OTHER

n/a

2000m

10A 40°C

Class I

rfi filter

via IEC connector

plastic ABS UL94-V0

-25/+85/21

UL94 V-2 min

25A 50/60Hz

93% RH non-condensing

500Vdc ≥3.5MR

IP40

0.8W/ph

0.35mA operating

0.28kg

Group IIIa

desktop

22yrs (MIL-HDBK-217F)

150% 60s

Category II

ASTM D7386

n/a

Degree II

resin

2.4kW

60V 1s

8mR/ph

5kA

15g 11mS

≥50mm ventilated surfaces

pluggable filter

1P 50/60Hz

IEC60320 C13 220mm lead, C14 plug

L-N 275V 6.5kA (350V)

5-55Hz 350um 55-500Hz 2G

230/240V (254V max)

2100Vdc 60s

CE/UKCA

PRODUCT LABEL

220 +20/-10mm

112.0

62.0

34.5

PRODUCT LABEL

220 +20/-10mm

112.0

62.0

34.5

PRODUCT LABEL

220 +20/-10mm

112.0

62.0

34.5

PRODUCT LABEL

220 +20/-10mm

112.0

62.0

34.5

PRODUCT LABEL

220 +20/-10mm

112.0

62.0

34.5