

DRF01

AKA

n/a

ALTITUDE

2000m

CURRENT

1A 40°C

CLASS

Class I

DEVICE

rfi filter

EARTHING

screw 0.2-2.5mm² 0.5Nm strip 8mm str

ENCLOSURE

plastic polyamide UL94-V0

ENVIRONMENT

-25/+85/21

FLAMMABILITY

UL94 V-2 min

GND BOND

25A 50/60Hz

HUMIDITY

93% RH non-condensing

INSULATION

500Vdc ≥3.5MR

IP RATING

IP20

LOSS

0.64W/ph

LEAKAGE

0.75mA operating

MASS

0.105kg

MATERIAL

Group IIIa

MOUNTING

Din Rail

MTBF

22yrs (MIL-HDBK-217F)

OVERLOAD

150% 60s

OVERVOLTAGE

Category II

PACKAGING

ASTM D7386

PCB

FR4 ZPMV2 105°C

POLLUTION

Degree II

POTTING

air

POWER

0.2kW

RESIDUAL

1v 5s

RESISTANCE

640mR/ph

SCCR

5kA

SHOCK

15g 11ms

SPACING

≥50mm ventilated surfaces

STYLE

DIN rail filter

SUPPLY

1P 50/60Hz

TERMINAL

screw 0.2-2.5mm² 0.5Nm strip 8mm str

VARIATOR

L-N 275V 6.5kA (350Vdc)

VIBRATION

5-55Hz 350um 55-500Hz 2G

VOLTAGE

230/240V (254V max)

WITHSTAND

2100Vdc 60s

EU/UK

CE/UKCA

US

CAN

OTHER

79.8

TER LBL

THIS WAY UP

79.2

PRODUCT LABEL

85.5 (EN50022 35x7.5)

90.5 (EN50035 32x15)

93 (EN50022 35x15)

22.4

73.6

PRODUCT LABEL

PRODUCT LABEL