ABF06

AKA	n/a
ALTITUDE	2000m
CURRENT	6A 40°C
CLASS	Class I
DEVICE	rfi filter
EARTHING	screw 4mm² 0.8Nm strip 7.5mm
ENCLOSURE	plastic ABS UL94-V0
ENVIRONMENT	-25/+85/21
FLAMMABILITY	UL94 V-2 min
GND BOND	25A 50/60Hz
HUMIDITY	93% RH non-condensing
INSULATION	500Vdc ≥3.5MR
IP RATING	IP20
LOSS	0.6W/ph
LEAKAGE	3.5mA operating
MASS	0.25kg
MATERIAL	Group IIIa
MOUNTING	M4 1.5Nm
MTBF	22yrs (MIL-HDBK-217F)
OVERLOAD	150% 60s
OVERVOLTAGE	Category II
PACKAGING	ASTM D7386
PCB	n/a
POLLUTION	Degree II
POTTING	resin
POWER	1.4kW
RESIDUAL	1v 5s
RESISTANCE	16.7mR/ph
SCCR	5kA
SHOCK	15g 11mS
SPACING	≥50mm ventilated surfaces
STYLE	terminal filter
SUPPLY	1P 50/60Hz
TERMINAL	screw 4mm² 0.8Nm strip 7.5mm
VARISTOR	n/a
VIBRATION	5-55Hz 350um 55-500Hz 2G
VOLTAGE	230/240V (254V max)
WITHSTAND	2100Vdc 60s
EU/UK	CE/UKCA
US	
CAN	
OTHER	









DELTRON Components | DELTRON Enclosures | ROXBURGH EMC | bcs | DEM | Alpha3 manufacturing

+44(0)1724 273200 | www.dem-uk.com

PROPRIETARY AND CONFIDENTIAL:

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF **ALPHA 3 MANUFACTURING**. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF **ALPHA 3 MANUFACTURING** IS PROHIBITED.

DEM Manufacturing is a division of Alpha 3 Manufacturing LTD

DEM Manufacturing, Deltron Emcon House, Hargreaves Way, Sawcliffe Ind. Park, Scunthorpe, North Lincolnshire, DN15 8RF, UK

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETRES
LINEAR & RADIAL TOLERANCE:
NO DECIMAL PLACES ±0.5mm
1 DECIMAL PLACE ±0.25mm
2 DECIMAL PLACES ±0.125mm
ANGULAR TOLERANCE: ±1°

IF IN DOUBT ASK! DO NOT SCALE DRAWING!

FINISH: -
MATERIAL: -

THE FINISHED PRODUCT SHOULD BE CLEAN AND FREE FROM ALL LIQUIDS AND DEBRIS. SURFACES SHOULD BE OF UNIFORM APPEARANCE FREE FROM SHARP EDGES, BURRS AND CORROSION

AUTHOR	Simon Williams
EDITOR	DB
APPROVER	DB
THIRD ANGLE PROJECTION	
SHEET 1 OF 1	
SCALE 1:1	A4
TITLE	GENERAL SPECIFICATION
FILE	ABF06
PART	
ISSUE/REV.	004
EDIT DATE	29/06/2023
RELEASE DATE	29/06/2023
	RELEASED