

ABF10

AKA

n/a

ALTITUDE

2000m

CURRENT

10A 40°C

CLASS

Class I

DEVICE

rfi filter

EARTHING

screw 4mm² 0.8Nm strip 7.5mm

ENCLOSURE

plastic ABS UL94-V0

ENVIRONMENT

-25/+85/21

FLAMMABILITY

UL94 V-2 min

GND BOND

25A 50/60Hz

HUMIDITY

93% RH non-condensing

INSULATION

500Vdc ≥3.5MR

IP RATING

IP20

LOSS

1W/ph

LEAKAGE

3.5mA operating

MASS

0.25kg

MATERIAL

Group IIIa

MOUNTING

M4 1.5Nm

MTBF

22yrs (MIL-HDBK-217F)

OVERLOAD

150% 60s

OVERVOLTAGE

Category II

PACKAGING

ASTM D7386

PCB

n/a

POLLUTION

Degree II

POTTING

resin

POWER

2.4kW

RESIDUAL

1v 5s

RESISTANCE

10mR/ph

SCCR

5kA

SHOCK

15g 11mS

SPACING

≥50mm ventilated surfaces

STYLE

terminal filter

SUPPLY

1P 50/60Hz

TERMINAL

screw 4mm² 0.8Nm strip 7.5mm

VARIATOR

n/a

VIBRATION

5-55Hz 350um 55-500Hz 2G

VOLTAGE

230/240V (254V max)

WITHSTAND

2100Vdc 60s

EU/UK

CE/UKCA

US

CAN

OTHER

PRODUCT LABEL

Ø4.5

6.0

85.0

6.0

12.0

70.0

97.0

1.2

PRODUCT LABEL

51.0

49.0