Hydro-Park 1127 & 1123 | widely adaptable

Some key features like cost-effective, simple construction, safe & comfort parking, etc. have made this parking lift popular and the best seller across years. The max lifting capacity of 2700kg covers 90% common vehicle weights, providing a simple way to create 2 dependent parking spaces above each other. They are widely used for valet parking, car storage and other commercial parking scenarios with attendant, either it's indoor or outdoor. Operation can be easily done by turning the key switch in front.


Specification

- Faster lifting speed with single cylinder
- For dependent parking
- Single platform for 2 vehicles
- Platform load capacity: 2300kg or 2700kg
- Vehicle height: up to 2050mm on ground floor
- Usable platform width: 2100mm as standard, up to 2500mm
- Automatic shut-off when operator releases key switch
- Stoppable at different heights to fit various vehicle & ceiling heights
- Auto lock release makes operation easier
- 24v control voltage avoids electric shock
- Sharing post feature allows tandem installations in minimum space
- Galvanized waving platform, high-heel friendly
- Low maintenance cost
- Fine surface coating supported by Akzo Nobel powders
- Free-standing design (optional) requires minimized construction cost
- Proven quality tested by TUV Germany; CE compliant




Dimensions









Hydro-Park 1123

Hydro-Park 1127

