





<i>Square Hollow</i>	<i>Description</i>	<i>Length</i>	<i>Finish</i>
	50x50x1.6mm	6.5	Mill, P/C
	50x50x3mm	6.5	Mill, WH, PR, MON
	65x65x2.5mm	6.5	Mill, P/C
	75x75x3mm	6.5	Mill
	90x90x2mm	3 / 4 / 6	Mill, P/C
	100x100x3mm	6.5	Mill, P/C
	125x125x3mm	6.5	Mill
	150x150x3mm	3 / 3.25 / 4 / 6 / 6.5	Mill, P/C

<i>Rectangular Beam</i>	<i>Description</i>	<i>Length</i>	<i>Finish</i>
	100x50x1.6mm	5 / 6.5 / 8	Mill, P/C
	100x50x3mm	5 / 6.5 / 8	
	150x50x2mm	4 / 6.5	
	150x50x3mm	5 / 6 / 6.5 / 8	
	200x50x3.0mm	5 / 6 / 6.5 / 8	
	250x50x3.0mm	7 / 8 / 9	Mill
	250x50x3/5mm	7 / 8 / 9	
	300x50x3mm	6.5 / 8	














<i>Angle</i>	<i>Description</i>	<i>Length</i>	<i>Finish</i>
	20x12x1.6mm	6.5	Mill, P/C
	20x20x1.6mm		
	40x25x1.6mm		
	40x40x1.6mm		
	50x25x1.6mm		
	50x50x1.6mm		
	70x25x1.6mm		

<i>Capping Channel</i>	<i>Description</i>	<i>Length</i>	<i>Finish</i>
	Light Duty 53x25x1.5	6500	P/C, Mill

<i>Colours</i>
White / Primrose / Paperbark / Black Satin / Woodland Grey / Monument

Internal Beam Connector	Description	Length	Finish
	43x30x3mm For 3mm Beams	4000	Mill
	45x32x3mm For 1.6mm Beams		

## Base Plate

<p>To Suit 45mm Post</p> 	<p>To Suit 50mm Post</p> 	<p>To Suit 65mm Post</p> 		
<p>To Suit 90mm Post</p> 	<p>To Suit 150mm Post</p> 	<p>To Suit 100mm Post</p> 		
<p>PTBC150 - ML Post To Beam Bracket</p> 	<p>Hot Dip Galvanised Flange Base Plate</p> <table border="0"> <tr> <td>  <p>Centre</p> </td> <td>  <p>Offset</p> </td> </tr> </table>		 <p>Centre</p>	 <p>Offset</p>
 <p>Centre</p>	 <p>Offset</p>			