

# EASYDET CLASSIC X EASYDET CLASSIC

**RF Dual Pedestal System**



Reliable and proven RF (Radio-Frequency) two-pedestal system with good detection of tags and adhesive labels. The Easydet system is suitable for most environments and has excellent resistance to challenging environments and other article surveillance systems.

The **RF Easydet system** is ideal for retailers located in shopping centers, who are looking for a standard loss prevention system that provides good, reliable protection. The aluminum pedestal frame is designed to provide a cost-effective solution while still maintaining a stylish and modern aesthetic not commonly found in comparable systems.

**Features & options**

- Variable design
- Low frequency option





Our Classic line of pedestals are available in three standard colours (silver, black and white) as well as two stylish options. The standard Classic pedestal is a lightweight, fully closed pedestal with opaque panels in one of our standard colour. The second option is transparent design with acrylic panels added to protect crossbars from possible damage at high traffic places.

## Design Comparison

SYSTEM COMPARISON	EASYDET CLASSIC X	EASYDET CLASSIC
<b>Features / Options</b>		
Advertisement Panel	✗	✗
Transparent Design	✓	✓
Integrated Metal Detection <sup>3</sup>	✗	✗
Integrated Visitor Counting <sup>3,5</sup>	✗	✗
Smart Directional Alarms <sup>3,4</sup>	✗	✗
Remote Maintenance & Diagnostics <sup>5</sup>	✗	✗
RGB Alarm Light	✗	✗
Power Saving Mode	✗	✗
Color Options	S / B / W	S / B / W
<b>Dimensions</b>		
Height	152.5 cm	152.5 cm
Width	29.4 cm	29.4 cm
Depth	5.2 cm	5.2 cm
Advertisement Panel (H x W)	✗	✗
Weight	6.3 kg	5.3 kg
<b>Detection Range</b>		
Detection Range Soft Labels <sup>1</sup> up to 95 / 190 cm	Dual up to 145 cm	Dual up to 145 cm
Detection Range Hard Tag <sup>2</sup> up to 95 / 190 cm	Dual up to 160 cm	Dual up to 160 cm
<b>Product Codes</b>		
Silver Colour	Receiver / Transmitter RS-ER30CLXS / RS-ET30CLXS	Receiver / Transmitter RS-ER30CLOS / RS-ET30CLOS
<b>System Specification</b>		
Operating frequency - 3.25-8.2 MHz		
Sweep frequency - 164 Hz		
Power - 24 V DC		
Consumption - 25 W		

Legend: ✓ included ✗ not available ○ optional

<sup>1</sup> tested with original DR labels in all orientations.

<sup>2</sup> tested with original AMERSEC® pencil tags in all orientations.

<sup>3</sup> minimum of 2 pedestals required. <sup>4</sup> visitor counting sensors required.

<sup>5</sup> e-COMM communication module required with a Storemonitor account.