




E.G.
UMBRELLAS

Single Offset Umbrella

SPECIFICATIONS



E.G. UMBRELLAS

Single Offset Umbrella

SPECIFICATIONS SUMMARY

Post & Arm	Square, Round - Aluminum or Steel
	Square - Iroko Wood
Thickness of Metal Parts	$\frac{1}{8}$
End Caps	UV-Resistant Plastic in Black, Brown, Grey, White
Hardware	304 Stainless Steel
Crank Mechanism	Marine Grade Galvanized Steel with Plastic Protective Cover & Auto Lock
Ribs	8 Aluminum $\frac{3}{4}$ " x $\frac{1}{2}$ "
Rib Thickness	$\frac{1}{16}$ "
Ribs Joint Protector	Protection Against Wear & Tear High Wind Stabilizer Bar
Multi-Option Bases	Inground, Surface Mount, Freestanding



Single Offset Umbrella

FRAME & STRUCTURE

Umbrella Frame	Cantilever
Number Of Ribs	8
Rib Measurements	$\frac{3}{4}$ " x $1\frac{1}{2}$ " X $5/64$ "
Post & Arm Measurements (Square)	3.5" x 3.5" x $5/64$ "

HARDWARE & COMPONENTS

Hardware	304 Stainless Steel
Crank Mechanism	Marine Grade Auto Lock Winch
End Caps	UV Resistant Plastic


Single Offset Umbrella

DIMENSIONS & HEIGHT

Canopy Height: Rib to Ground (Open)	8' – 8'6"
Rib to Ground (Closed)	1'8" – 4'5"
Top to Ground	10'10" – 11'6"

BASE & STABILITY

Base: Inground, Surface Mount	18" x 18"
Freestanding Base	6" x 12" 20" x 46" 40" x 47"
Base Counterweight	550 – 1100 lbs



Single Offset Umbrella

FEATURES & OPTIONS

High Wind Stabilizer Bar	Standard	Soltis PVC Fabric	Optional
Umbrella 360° Rotation	Standard	Air Soltis	Optional
Rib Joint Protector	Standard	Canopy Tilt	Optional
Wind Roof Canopy	Standard	Retractable Arm	Optional
Acrylic Fabric	Standard	Valance	Optional
Multi Vent Canopy	Optional	Fabric & Velcro Gutters	Optional
Double Fabric	Optional	Logo	Optional

E.G. UMBRELLAS