

PRODUCT IMAGE

**Leoprint**  
**Soft-Touch Mono-Paper envelope**  
 Barrier paper envelope (Alu-Free)  
 - Monomaterial (<5% Coating)  
 - Aroma barrier  
 - Premium tactile finish

LEOPRINT, UAB  
 V.A. (rašono str. 32)  
 LT-0244, Vilnius, Lithuania  
 +370 699 94899  
 info@leoprint.eu  
 www.leoprint.eu

SCAN ME!

PAP 22

Recycle with paper

Premium haptics, pure recyclability.

Sensory experience: the premium "soft-touch" feel without using plastic films.  
 - Performance: high quality printing and heat-seal properties with functional barrier protection.  
 - Recyclability: Paper and board - recyclability laboratory test method - Part 1: recycling mill with conventional process.  
 Material: FSC® Mixed 70 (paper base).  
 Structure: Monomaterial (<5% dry coating weight).

MATERIAL COMPOSITION SUMMARY

Station	Anilox	Wet Transfer g/m <sup>2</sup>	Coverage %	Mix Solids %	Dry Solids g/m <sup>2</sup>
Station 1	S-800	1.5	12	29.48	0.05
Station 2	S-800	1.5	7	26.43	0.03
Station 3	S-800	1.5	7	22.3	0.02
Station 4	S-800	1.5	8	31.45	0.04
Station 5	S-800	1.5	100	36	0.54

Component	Value (g/m <sup>2</sup> )
Base Coating (HS/Barrier)	2.49
Printing Solids	0.68
Total Non-substrate	3.17
Substrate Weight	70

RECYCLABILITY STATUS

Non-substrate Ratio:	4.49%
Classification:	PAP 22 (Recyclable)