



## Polyester Mesh (80%) – Bleacher Wrap

**Colors:** All standard colors

Mechanical Properties	Warp	Fill
Adhesion (5970)	7 $\pm$ 2 lbs/2 in.	7 $\pm$ 2 lbs/2 in.
Tensile Strength (5100)	220 $\pm$ 20 lbs/in.	260 $\pm$ 20 lbs/in.
Tear Strength (5134)	90 $\pm$ 20 lbs	90 $\pm$ 20 lbs

Physical Properties	
Weight	9 Oz/Yd Sq. +/- 0.5
Base Fabric	9x12 1000 Denier Poly WI Flat
Embossing	None

Other Properties	
Fire Retardant	Various Colors ONLY - Call For Info (Test Method: MVSS302)
Heat Sealability	Yes
Shade Screen Factor	80%
Air Permeability	> 340 CFM/F Sq.
Burst Strength ASTM D 751	320 Lbs/2 Inches

**Disclaimer:** Information from Collins Company is based on data believed reliable but provided only as reference averages, not specifications. The purchaser is solely responsible for determining suitability for use. Collins Company assumes no liability and disclaims all warranties, express or implied, including merchantability, fitness for purpose, or any arising from trade, and this document is not engineering advice.

### California

300 East Eucalyptus Avenue  
Ontario, CA 91762

[collinscompany.com](http://collinscompany.com)

Call (800) 222-4348  
Fax (909) 548-6908

### Georgia

1375 Weber Industrial Drive  
Cumming, GA 30041