



## 18 Oz. Vinyl (100%)

**Colors:** All Standard Colors

	<b>Value</b>	<b>Test Method / Notes</b>
Base Fabric (100% Polyester)	1000D x 1300D / 18 x 17	
Weight	18 oz / yard <sup>2</sup>	FS-191-5041
Tensile Strength (Grab)	410 lbs x 410 lbs	FS-191-5100
Tensile Strength (Strip)	300 lbs x 300 lbs	FS-191-5102
Tear Strength (Tongue)	100 lbs x 100 lbs	FS-191-5134
Adhesion Strength	12 x 10 lbs / inch	FS-191-5970
Abrasion Resistance	400 cycles	FS-191-5306
Hydrostatic Resistance	At least 600 lbs / inch <sup>2</sup>	FS-191-5512
U.V. Resistance	Not excessive fading after 300 HRS	Weather-O-Meter
Cold Crack Resistance	-40° F	FS-191-5874
High Temperature Resistance	180° F (Does not Block)	FS-191-5872
Flame Resistance	Available (Special Order)	

**Disclaimer:** Information from Collins Company is based on data believed reliable but provided only as reference averages, not specifications. The purchaser is solely responsible for determining suitability for use. Collins Company assumes no liability and disclaims all warranties, express or implied, including merchantability, fitness for purpose, or any arising from trade, and this document is not engineering advice.

### California

300 East Eucalyptus Avenue  
Ontario, CA 91762

### [collinscompany.com](http://collinscompany.com)

Call (800) 222-4348  
Fax (909) 548-6908

### Georgia

1375 Weber Industrial Drive  
Cumming, GA 30041