

DURACELL®



CEF22-GBL3

Hi Speed Multi

Duracell Rechargeable



Specifications	
Battery Charger:	Class 2, Power Supply
Plug:	AC/DC Adapter Wall Plug
Battery Type/Fit:	NiMH: 1 to 4 AA/HR6, 1 to 4 AAA/HR03, 1 – 4 C/HR14, 1 – 4 D/HR20, 1 9V
Typical Weight:	330.5g
Input:	100-240V AC, 50-60 Hz, 7.2w
Output:	1 – 2 AA/2C/2D: 1350mA 1 – 2 AAA: 750mA 3 – 4 AA/AAA/C/D: 750mA 9V: 32mA
Operating Temp:	0°C - 35°C (32°F - 95°F)
Dimensions:	156mm x 101mm x 59mm

FEATURES	Charge Time: 1 hour
	LED Charge Status Indicators
	Charges 1 to 4 batteries at a time
INDICATION	Solid Red = Charging
	Solid Green = Charged
	Blinking Red = Error/Bad Battery
	Off = No Battery
SAFETY	Over Voltage Protection
	Low Voltage Protection
	Reverse Polarity Protection
	Short Circuit Protection
	Primary Cell Protection
	Over Temperature Protection
	Low Temperature Protection
	Overcharge Protection
	Safety Timer

Information and contents in this data sheet are for reference purposes only. They do not constitute any warranty and representation is subject to change without notice. For most current information and further details, please contact Duracell.