

DURACELL®



CEF7NA1

Ion Speed 500

Duracell Rechargeable



Specifications	
Battery Charger:	Class 2, Integrated Power Supply
Plug:	Direct Plug in Matches Local Requirements
Battery Type/Fit:	NiMH: 2 or 4 AA/HR6, NiMH: 2 or 4 AAA/HR03
Typical Weight:	103g
Input:	100-240V AC, 50-60 Hz, 7w
Output:	AA/HR6: 3.0V DC 250mA AAA/HR03: 3.0V DC 125mA
Operating Temp:	0°C - 35°C (32°F - 95°F)
Dimensions:	118mm x 72mm x 76.4mm

FEATURES	Charge Time: 8 to 14 hours
	500mW Charge Power
	LED Charge Status Indicators
	Works with all AA and AAA NiMH batteries
	Charges 2 or 4 batteries at a time
INDICATION	Solid Red = Charging
	Solid Green = Charged
	Blinking Red = Error/Bad Battery
	Off = No Battery
SAFETY	Over Voltage Protection
	Low Voltage Protection
	Reverse Polarity Protection
	Short Circuit Protection
	Primary Cell Protection
	Over Temperature Protection
	Low Temperature Protection
	Overcharge Protection
	Safety Timer

Information and contents in this data sheet are for reference purposes only. They do not constitute any warranty and representation is subject to change without notice. For most current information and further details, please contact Duracell.