



T-BRANCH

Tee Branches, or T-branches, are duct fittings used to create a 90° branch off a main duct line, forming the shape of a “T.” They are commonly used in positive pressure systems where air is being pushed through the ducts. Due to their design, they are not recommended for negative pressure systems, as the branch line can experience reduced airflow caused by increased static pressure.

Øin.	Length in.	Weight Lbs.
3	B + 8"	1.5
4		2
5		2.8
6		3.3
7		4
8		4.8
9		5.5
10		6
11		7.5
12		8.8
13		10.3
14		12
15		13.3
16		14
17		16
18		18.3
19		19.5
20		20.5
21		22
22		24.8
23		27
24		29
25		34.5
26		40.3
27		43
28		45
29		52
30		58.5
31		61
32		63
33		65
34		66.4
35		68.2
36		70.3
37		72.5
38		75.7
39		77.4
40		80.4



SNAPLOCK MATERIAL OPTIONS

GALVANIZED				STAINLESS STEEL			
Gauges	Size in			Gauges	Size in		
	Min Øin.	Max Øin.			Min Øin.	Max Øin.	
STD.	22	3	12	STD.	22	3	12
	20	13	24		20	13	24
OPT.	18	4	24	OPT.	18	8	24
	16	8	24		16	8	24
	14	8	24				

FLANGED MATERIAL OPTIONS

GALVANIZED				STAINLESS STEEL			
Gauges	Size in			Gauges	Size in		
	Min Øin.	Max Øin.			Min Øin.	Max Øin.	
STD.	22	3	12	STD.	22	3	12
	20	13	24		20	13	24
	18	26	30		18	26	30
	16	32	40		16	32	40
	14	42	50	OPT.	20	4	12
	12	52	72		18	4	24
OPT.	20	4	12		16	8	30
	18	4	24				
	16	8	30				
	14	8	50				
	12	10	72				
	10	12	72				