



SOLID
TO SUCCEED



ROUGH TERRAIN SCISSOR LIFT

XG1823ERT

Comply with CE

Standard configuration

- Foldable guardrail
- Platform self-locking door
- Dual slide-out platform extension deck
- Anti-slipping metal platform
- Boom safety maintenance support
- Pull-out engine tray
- Standard Forklift pocket for transport
- Lanyard connection point
- Fixing and lifting points
- 4-wheel drive
- Front-wheel steering
- Movement alarm
- Strobe light
- Electric horn
- Emergency stop button
- Battery power display
- Full proportion travel and lift control
- High-altitude automatic limit travel protection
- Limiting position deceleration and limit protection
- Outrigger leveling system
- Tilt protection system
- Charging protection system
- Auto brake system
- Fault diagnosis system
- Emergency lowering system
- Leveling outrigger support detection system
- Wheel-side traveling motor state monitoring and overtemperature stall protection system
- Weighing alarm system
- Axle oscillation system



Working height
18.1 meters



Lift capacity
700Kg



Electric
power



Optional configuration

- High-altitude low speed travel
- Chassis protective fence
- Non-marking rubber tire
- Platform anti-collision

XCMG FIRE-FIGHTING SAFETY EQUIPMENT CO.,LTD

No.17 Zhujiang East Road, Hi-Tech Development Zone, Xuzhou, Jiangsu, China
mewp@xcmg.com

XG1823ERT




SOLID
TO SUCCEED


Rough Terrain Scissor Lift-Electric

Item	Metric
Dimension	
Overall length (without ladder/outriggers)	4860mm(—)
Overall width	2286mm
Overall height (platform folded)	3170(2510)mm
Platform length	3980mm
Platform width	1830mm
Subplatform extension length	1450mm/1140mm
Guardrail height	1100mm
Toeboard height	150mm
Outrigger span (side to side/front and rear)	1995mm/4280mm
Wheelbase	2850mm
Min. ground clearance (pothole protection deployed/undeployed)	253mm(—)
Performance	
Max. working height	18,1m
Max. platform height	16,1m
Min. platform height	2m
Max. driving height	3,6m(Standard) 9,1m(optional)
Rated load	700kg
Subplatform rated load	230kg
Max. number of occupants (indoor/outdoor)	4/4
Max. driving speed (stowed)	5,1km/h
Max. driving speed (raised)	0km/h(Standard) 1,1km/h(optional)
Max. gradeability	40%
Min. turning radius (inside)	2,5m
Min. turning radius (outside)	5,6m
Platform raising time	75s
Platform lowering time	55s
Max. working slope (side to side/front and rear)	2°/3°
Outrigger leveling angle (side to side/front and rear)	/
Power source	
Battery voltage	48V
Battery capacity (5HR)	480Ah
Battery charger	48V/35A
Traveling motor	3,3kW/32V
Lifting motor	12kW/31V
Hydraulic tank capacity	100L
Tire	
Tire size	835mm×290mm
Tire ground pressure	13,3kg/cm ²
Driving wheels	4
Braking wheels	4
Steering wheels	2
Weight	
Total weight	8380kg

Stowed



Trans



The print does not belong to the contract, nor a part of the commercial contract. We reserve the right to revise the product model, parameters, configuration based on the continuous improvement requirements of the product, without prior notice. Pictures are for reference only, and the specific product shall depend on the real product. The final interpretation rights belong to XCMG.