

HiTac Self-Adhesive Product Specification



Product Description and Applications

HiTac Self-Adhesive is ideally suited to applications where label durability is required when a product has an uneven surface. The strong adhesive makes sure your product will be identified from the start of your process all the way through to it's final destination.

Industries that currently utilise HiTac Self-Adhesive include:

Metals
Concrete
Recycling

Brick & Block
Engineering
Chemicals

Printability

HiTac Self-Adhesive can be pre-printed to one side in up to 6 colours. It can also be over-printed using a suitable thermal transfer printer and ribbon combination recommended by Refine AB.

Storage Guidelines

Keep this product out of direct sunlight in temperatures between 25°C - 28°C at 40-50% humidity. Prolonged storage at higher or lower temperatures may affect the shelf-life of this product.

Thickness	Micron - 60 +/- 10%
Material Weight	Grams per Square Metre - 152 +/- 10%
Adhesive Coat Weight	Grams per Square Metre - 50 +/- 5%
Adhesive Type	Hot melt -rubber resin
Application Temperature	<0°C
Temperature Resistance	-20°C to +50°C

The above values and information are given in good faith but without warranty. Refine AB recommends the testing of samples to ascertain suitability. It is the responsibility of the end user to satisfy the suitability of the product for the application. All goods are supplied in accordance with our standard conditions of sale.

Refine AB

Email: hej@refine-labels.com

Website: www.refine-labels.com