

DESCRIPTION

Based on a water-based pure acrylic resin and reinforced with a special pigment extender, Dyno Stucco Textures is a heavy-body textured finish suitable for both interior and exterior wall coatings. It is extremely tough and provides excellent adhesion to concrete, plastered surfaces, asbestos sheets, and gypsum boards. Dyno Stucco Textures can be applied using a texture spray gun or a patterned roller. The elegant texture pattern effectively masks any hairline cracks or minor imperfections on masonry surfaces.

PRODUCT FEATURES AND RECOMMENDED USES

Ideal for the application of office building, condominium, housing, or any new and old masonry surface, both interior and exterior.

TECHNICAL DATA

Type	100% Pure Acrylic Emulsion
Color	Grayish White
Texture	Matt
Non-Volatile	70 - 75 % by volume
Coverage (Theoretical)	3 - 5 sq.m./Gallon
Application	By Pattern Roller Spray with the following recommendation:
	Nozzle Tip 6 - 10 mm.
	Pressure 5 - 7 kgs/sq.cm
	Compressor 2 HP minimum
Diluent	Water, using sparingly if necessary
Drying Time	Touch Dry 1 - 2 hours
(21-27°C and 50% RH)	Hard Dry 8 - 10 hours
	Re-Coat 10 - 16 hours

SURFACE PREPARATION

For re-painting, make sure the surface to be painted is free from dirt, grease, waxy contaminants, and loose or peeling paint. If mold and fungus appear on the painted surfaces, it is important to remove all existing mold before applying a new coat of paint. One effective method for killing mold is to wash the affected surfaces with Dyno Super Mold Killer. The treated surfaces should then be rinsed with clean water and allowed to dry before repainting.

SUGGESTED COATING SYSTEMS

For New Masonry Surfaces

Dyno Alkali Resisting Primer P-1000	1 Coat
Dyno Stucco Textures	1 Coat
Dynosilk or Dynolux	2 Coats

For Repainting

Dyno Chalking Sealer P-1100	1 Coat
Dyno Stucco Textures	1 Coat
Dynosilk or Dynolux	2 Coats