

DESCRIPTION

Acrylic emulsion paint with a matte finish, designed to effectively cover ceiling joints for a smooth and uniform appearance.

PRODUCT FEATURES AND RECOMMENDED USES

Suitable for interior ceiling applications.

TECHNICAL DATA

Type	Acrylic Emulsion
Color	C-777 White, C-999 Grey, C-888 Lavender
Texture	Matt
Non-Volatile	32 - 38% by volume
Coverage (Theoretical)	33 - 40 sq.m./Gallon
Wet Film Thickness	100 - 110 microns
Dry Film Thickness	35 - 40 miicrons
Application	Brush, Roller or Spray
Diluent	Clean Water
	Brush, Roller 15 – 30% by volume
	Spray 20 – 35% by volume
Drying Time	Touch Dry 20 - 30 minutes
	Hard Dry 1 - 2 hours
	Recoat Dry 2 hours

SURFACE PREPARATION

Clean the surface thoroughly, ensuring it is free from dirt, grease, or peeling paint. If the surface has moss or mold, clean it with DYNOL Mold Killer and rinse thoroughly with water to remove all traces of the solution. Allow the surface to dry completely before painting. For cracks less than 1 mm wide, fill them with DYNOL Acrylic Filler and sand the area until smooth.

SUGGESTED COATING SYSTEMS

For Ceiling - Interior

Dynopro Contact Primer P-1400	1 Coat
DYNOPRO Max Ceiling Paint	2 Coats