

DESCRIPTION

Voqe is a 100% acrylic emulsion paint, available in a premium grade with semi-gloss finish and a regular grade with a satin sheen look. It gives performance of washability, UV protection, low dirt pick up on film, anti fungus and algae resistance, it contains no added lead and mercury.

PRODUCT FEATURES AND RECOMMENDED USES

It is ideal for application to both exterior and interior concrete, new and masonry surface, especially for office building, condominium and masonry concrete structure which require long lasting protection.

TECHNICAL DATA

Type	100% Acrylic Emulsion
Color	According to Voqe Color Card
Texture	Semi-gloss and Sheen
Non-Volatile	35 – 37 %by volume
Coverage (Theoretical)	35 - 40 sq.m./U.S.Gallon Coat at 35 – 40 microns/coat
Wet Film Thickness	100 - 110 microns/coat
Dry Film Thickness	35 - 40 microns/coat
Drying Time	Touch Dry 20 - 30 minutes Hard Dry 1 - 2 hours Re-Coat 1 - 2 hours
Application	Brush, Roller and spray
Diluent	Clean Water Brush, Roller 10 – 15 % by volume Air Spray 20 – 30 % by volume

SURFACE PREPARATION

For re-painting, make sure the surface to be painted is free from dirt, grease any waxy contaminant, loose peeling paint. If mold and fungus appear in the painted surfaces, it is important that all existing mold be killed before applying a new coat of paint. One of the effective method for killing mold is to wash the mold infested surfaces with Dyno super mold killer. The treated surfaces is then rinsed with clean water and allow to dry before repainting.

For new masonry surface, leave the surface to be completely dried for a minimum of 30 days or measure moisture which should be less than 14% on the surface with protimeter mini. Before painting, make sure the surface to be painted is free from dirt, grease and waxy contaminant.

SUGGESTED COATING SYSTEMS

For New Masonry Surfaces

Voqe Alkali Resisting Primer	1 Coat x 45 - 55 microns/coat
Voqe 100% Acrylic Emulsion	2 Coats x 30 - 40 microns/coat

For Repainting

Voqe Chalking Sealer	1 Coat x 10 - 15 microns/coat
Voqe 100% Acrylic Emulsion	2 Coats x 30 - 40 microns/coat