

DESCRIPTION

Based on lightfast pigments and pure acrylic latex, Dyno Acrylic Emulsion is a high-quality acrylic emulsion paint for interior finishes where a washable, hard-wearing, low-sheen finish is required. It is characterized by good resistance to discoloration on masonry surfaces.

PRODUCT FEATURES AND RECOMMENDED USES

Ideal for interior decoration on concrete, both new and old masonry surfaces, such as plaster, brick, asbestos, and shingles.

TECHNICAL DATA

Type	100% Pure Acrylic Emulsion		
Color	Dyno Acrylic Emulsion Color Card		
Texture	Matt		
Non-Volatile	40 - 45 % by volume		
Coverage (Theoretical)	35 - 45 sq.m./Gallon		
Wet Film Thickness	90 - 100 microns		
Dry Film Thickness	35 - 45 microns		
Application	Brush, Roller or Spray		
Diluent	Clean Water		
Drying Time (21-27°C and 50% RH)	Brush, Roller	10 – 15%	by volume
	Air spray	20 - 30%	by volume
	Touch Dry	20 - 30	minutes
	Hard Dry	1 - 2	hours
	Re-Coat	1 - 2	hours

SURFACE PREPARATION

For re-painting, make sure the surface to be painted is free from dirt, grease, waxy contaminants, and loose, peeling paint. If mold and fungus appear on the painted surfaces, it is important that all existing mold be killed before applying a new coat of paint. One effective method for killing mold is to wash the mold-infested surfaces with Dyno Super Mold Killer. The treated surfaces should then be rinsed with clean water and allowed to dry before repainting.

For new masonry surfaces, allow the surface to completely dry for a minimum of 30 days. Before painting, make sure the surface is free from dirt, grease, and waxy contaminants.

SUGGESTED COATING SYSTEMS

For New Masonry Surfaces

Dyno Alkali Resisting Primer P-1000	1 Coat
Dyno Pure Acrylic for Interior	2 Coats

For Repainting

Dyno Chalking Sealer P-1100	1 Coat
Dyno Pure Acrylic for Interior	2 Coats