

DESCRIPTION

High-quality nitrocellulose acrylic spray paint with a thick color formulation, fast-drying, and good adhesion.

PRODUCT FEATURES AND RECOMMENDED USES

Dyno spray paint is available in both standard and metallic shades. It can be used on various materials such as metal and wood. The standard shades are suitable for both indoor and outdoor applications, while the metallic shades are ideal for indoor use. It is perfect for spraying items that require a beautiful, shiny paint film. It is not recommended for areas with frequent contact. To enhance the durability of the paint film, it is suggested to apply a topcoat with 7101 Gloss Clear, which will make the film glossier but slightly reduce the metallic shine.

TECHNICAL DATA

Type	Acrylic Nitrocellulose		
Color	TOPCOAT		
	7101 Gloss Clear	7102 Gloss White	7103 Gloss Black
	7104 Light Gray	7105 Deep Gray	7106 Safety Green
	7107 Safety Blue	7108 Safety Red	7109 Safety Yellow
	7201 Satin Clear	7202 Matt White	7203 Matt Black
	METALLIC		
	7301 Metallic Gold	7302 Metallic Silver	7303 Metallic Rose Gold
	7304 Metallic Copper	7305 Metallic White Pearl	
	PRIMER		
	7401 White Primer	7402 Gray Primer	
Texture	Gloss, Matte, Metallic		
Coverage (Theoretical)	1.5 - 2.0 sq.m./can/coat		
Dry Film Thickness	15 - 25 microns		
Drying Time	Touch Dry	15 - 20	minutes
	Hard Dry	1 - 2	hours
	Recoat	10 - 15	minutes

Note: Do not spray paint on rainy days or when humidity is high, as it can cause the paint film to lack gloss or the metallic film to lose its shine.

SURFACE PREPARATION

The surface to be painted must be dry and clean, free from dust, rust, grease, oil stains, and peeling old paint. Scrape off the deteriorated paint film and rust using a wire brush or power sander, then clean the surface with thinner and allow it to dry completely. Shake the can for about 1-2 minutes until you hear the ball inside rattling evenly. Spray from a distance of about 15-20 cm from the workpiece. Shake the can periodically while spraying. Avoid applying the paint too thickly in one go. It is recommended to apply several thin layers to prevent the paint from wrinkling or dripping.

SUGGESTED COATING SYSTEMS

For Steel Steel

White Primer, Gray Primer	1 - 2 coats
Topcoat	2 coat