

DESCRIPTION	

It is designed as a primer for interior and exterior use on masonry surfaces (old construction or renovation) before applying the topcoat.

PRODUCT FEATURES AND RECOMMENDED USES

Dyno Chalking Sealer White P-1222 is an acrylic water-based primer designed for use as a pigmented sealer. It is specially developed for old painted surfaces with a chalky condition.

TECHNICAL DATA

Type	Acrylic Emulsion		
Color	White		
Texture	Matt		
Non-Volatile	45 - 50 % by volume		
Coverage (Theoretical)	35 - 40 sq.m./Gallon		
Wet Film Thickness	70 - 80 microns/coat		
Dry Film Thickness	35 - 40 microns/coat		
Application	Brush, Roller		
Diluent	Clean Water	5 - 10 % by volume	
Drying Time (21-27°C and 50% RH)	Touch Dry	30 - 60	minutes
	Hard Dry	1 - 2	hours
	Re-Coat	1 - 2	hours

SURFACE PREPARATION

For re-painting, make sure the surface to be painted is free from dirt, grease, waxy contaminants, and loose or peeling paint. If mold and fungus appear on the painted surfaces, it is important to remove all existing mold before applying a new coat of paint. One effective method for killing mold is to wash the affected surfaces with Dyno Super Mold Killer. The treated surfaces should then be rinsed with clean water and allowed to dry before repainting.

For new masonry surfaces, allow the surface to dry completely for a minimum of 30 days. Before painting, ensure the surface is free from dirt, grease, and waxy contaminants.

SUGGESTED COATING SYSTEMS

For Repainting On The Chalky Painted Surfaces

Dyno Chalking Sealer WB (White) P-1222	1	Coat
Dyno Acrylic Emulsion / Dynopro / Dynolux / Dynosilk	2	Coats