

Dyno Multi-Purpose Primer P-1900 is a pigmented concrete primer made from special acrylic resin. It is ready to use and easy to apply. Environmentally friendly, with no added lead or mercury.

Dyno Multi-Purpose Primer is based on a super acrylic solvent base, designed for use as a pigmented primer. It is suitable for both fresh and old concrete, offering high penetration and excellent adhesion.

Type	Acrylic Resin, Solvent Type		
Color	White		
Texture	Matt		
Non-Volatile	42 – 46% by volume		
Coverage (Theoretical)	35 - 40 sq.m./Gallon		
Wet Film Thickness	75 - 80 microns		
Dry Film Thickness	25 - 35 microns		
Application	Brush and Roller		
Diluent	Ready to use. Normally not required. If necessary use Dyno Thinner No.2		
Drying Time	Touch Dry	30 - 60	minutes
(21-27°C and 50% RH)	Hard Dry	1 - 2	hours
	Recoat Dry	2	hours

For re-painting, make sure the surface to be painted is free from dirt, grease, waxy contaminants, and loose, peeling paint. If mold and fungus appear on the painted surfaces, it is important that all existing mold be killed before applying a new coat of paint. One effective method for killing mold is to wash the mold-infested surfaces with Dyno Super Mold Killer. The treated surfaces should then be rinsed with clean water and allowed to dry before repainting.

For New Masonry Surfaces/Re-painting Surface

Dyno Multi-purpose Primer P-1900	1 Coat
Dyno Acrylic Emulsion/ Dynopro/ Dynolux/ Dynosilk	2 Coats