

DESCRIPTION

An alkyd-based primer specially formulated for use with alkyd enamel. It is quick-drying, fungus-resistant, offers good leveling, and has high opacity. It also provides good intercoat adhesion between the primer and the topcoat enamel.

PRODUCT FEATURES AND RECOMMENDED USES

Most suitable as an undercoat for wood, primed metal, or masonry surfaces before the final finish with High Protective Paint.

TECHNICAL DATA

Type	Synthetic Alkyd
Color	White
Texture	Matt
Non-Volatile	35 - 40% by volume
Coverage (Theoretical)	40 - 45 sq.m./Gallon
Wet Film Thickness	85 - 95 microns
Dry Film Thickness	30 - 35 microns
Application	Brush, Roller or Spray
Diluent	Dyno Thinner No.1
	Brush, Roller 5 - 10% by volume
	Air Spray 10 - 20% by volume
Drying Time	Touch Dry 1 - 1.5 hours
	Hard Dry 8 - 10 hours
	Recoat Dry 8 - 10 hours

SURFACE PREPARATION

Make sure the surface to be painted is free from dirt, grease, waxy contaminant and loose peeling paint. Crack and open grain should be properly sealed and sand smooth before priming.

SUGGESTED COATING SYSTEMS

Normal Hard Wood

Dyno EX Universal Undercoat X-5000	1 Coat
Dyno EX High Gloss Enamel	2 Coats

Resinous Wood

Dyno Aluminum Wood Primer	1 Coat
Dyno EX Universal Undercoat X-5000	1 Coat
DYNO EX High Gloss Enamel	2 Coats