

DESCRIPTION

It is an ideal primer specially formulated for new masonry surfaces where alkalinity is the main cause of premature paint degradation. Because it is based on a special pure acrylic binder, DYNO EX Alkaline Resisting Primer effectively resists saponification on new plastered surfaces, asbestos, and new cement.

PRODUCT FEATURES AND RECOMMENDED USES

An ideal masonry primer for application on new concrete, asbestos sheet, ceiling, plaster, for both interior and exterior.

TECHNICAL DATA

Type	Acrylic Emulsion
Color	Off-white
Texture	Matt
Non-Volatile	40 - 45% by volume
Coverage (Theoretical)	35 - 45 sq.m./Gallon
Wet Film Thickness	85 - 110 microns
Dry Film Thickness	35 - 45 microns
Application	Brush, Roller or Spray
Diluent	Clean Water
Drying Time	Brush, Roller 10 - 20% by volume
	Spray 20 - 35% by volume
	Touch Dry 20 - 30 minutes
	Hard Dry 1 - 2 hours
	Recoat Dry 1 - 2 hours

SURFACE PREPARATION

For repainting, make sure the surface to be painted is free from dirt, grease, waxy contaminants, and loose peeling paint. If mold and fungus appear on the painted surfaces, it is important to kill all existing mold before applying a new coat of paint. One effective method for killing mold is to wash the mold-infested surfaces with Dyno Super Mold Killing Solution. The treated surface should then be rinsed with clean water and allowed to dry before repainting.

For new masonry surfaces, allow the surface to dry completely for a minimum of 30 days. Before painting, ensure that the surface is free from dirt, grease, and waxy contaminants.

SUGGESTED COATING SYSTEMS

For New Masonry Surface

Dyno EX Alkaline Resisting Primer X-7000	1 Coat
Dyno EX Acrylic Paint For Exterior or Interior	2 Coats