

## DESCRIPTION

Dyno Chalking Sealer is a special surface conditioner for re-painting masonry surfaces where the old paint is deteriorated or chalky. Due to its deep penetrative properties, it transforms the chalky surface into a solid foundation for subsequent coatings.

## PRODUCT FEATURES AND RECOMMENDED USES

It is ideal for priming chalky painted surfaces. Dyno Chalking Sealer will transform chalky surfaces into a sound substrate for re-painting.

## TECHNICAL DATA

<b>Type</b>	Acrylic Resin, Solvent Type
<b>Color</b>	Clear
<b>Texture</b>	Glossy
<b>Non-Volatile</b>	18 – 20 % by volume
<b>Coverage (Theoretical)</b>	50 - 55 sq.m./Gallon
<b>Wet Film Thickness</b>	60 - 70 microns
<b>Dry Film Thickness</b>	10 - 15 microns
<b>Application</b>	Brush, Roller or Spray
<b>Diluent</b>	Normally not required. If necessary, use Dyno Thinner No.2
<b>Drying Time</b> (21-27°C and 50% RH)	Touch Dry 30 - 45 minutes Hard Dry 1 - 2 hours Re-Coat 1 - 2 hours

## SURFACE PREPARATION

For re-painting, make sure the surface to be painted is free from dirt, grease, waxy contaminants, and loose or peeling paint. If mold and fungus appear on the painted surfaces, it is important to remove all existing mold before applying a new coat of paint. One effective method for killing mold is to wash the affected surfaces with Dyno Super Mold Killer. The treated surfaces should then be rinsed with clean water and allowed to dry before repainting.

## SUGGESTED COATING SYSTEMS

### For Re-painting On The Chalky Painted Surface

Dyno Chalking Sealer P-1100	1 Coat
Dyno Acrylic Emulsion / Dynopro / Dynolux / Dynosilk	2 Coats