

DESCRIPTION

Dyno Acrylic Primer P-2710 is a water-based acrylic primer specially developed for use with Dyno Acrylic products. The undertone of this primer enhances the topcoat, providing better coverage and optimal gold luster.

PRODUCT FEATURES AND RECOMMENDED USES

Used as a primer for Dyno Gold Water-Based Paint 2700 on walls, concrete, wood, alloys, and metal surfaces that have been properly primed.

TECHNICAL DATA

Type	Acrylic Emulsion
Color	Yellow
Texture	Low Sheen Matt
Non-Volatile	40 - 45 % by volume
Coverage (Theoretical)	35 - 45 sq.m./Gallon
Wet Film Thickness	90 - 100 microns
Dry Film Thickness	35 - 45 microns
Application	Brush, Roller or Spray
Diluent	Clean Water
	Brush, Roller 10 – 15 % by volume
	Air spray 20 - 30 % by volume
Drying Time	Touch Dry 20 - 30 minutes
	Hard Dry 1 - 2 hours
	Re-Coat 1 - 2 hours

SURFACE PREPARATION

For re-painting, make sure the surface to be painted is free from dirt, grease, waxy contaminants, and loose or peeling paint. If mold and fungus appear on the painted surfaces, it is important to remove all existing mold before applying a new coat of paint. One effective method for killing mold is to wash the affected surfaces with Dyno Super Mold Killer. The treated surfaces should then be rinsed with clean water and allowed to dry before repainting. For new masonry surfaces, allow the surface to dry completely for a minimum of 30 days. Before painting, ensure the surface is free from dirt, grease, and waxy contaminants.

SUGGESTED COATING SYSTEMS

For New Masonry Surfaces

Dyno Alkali Resisting Primer P-1000	1 Coat
Dyno Acrylic Primer P-2710	1 Coat
Dyno Acrylic Emulsion Gold 2700	2 Coats

Re-painting

Dyno Chalking Sealer P-1000	1 Coat
Dyno Acrylic Primer P-2710	1 Coat
Dyno Acrylic Emulsion Gold 2700	2 Coats

Metal Alloy

Dyno Wash Primer, Dyno Metal Conditioner	1 Coat
Dyno Acrylic Primer P-2710	1 Coat
Dyno Acrylic Emulsion Gold 2700	2 Coats