

DESCRIPTION

Acrylic water-based surface conditioner.

PRODUCT FEATURES AND RECOMMENDED USES

A low-odor product with good penetrating power, it is specially developed for old painted surfaces in chalky condition. Dyno Chalking Sealer is capable of binding powdery materials into a sound surface for recoating and is more suitable when a low-odor coating is required.

TECHNICAL DATA

Type	Water base, Acrylic Emulsion		
Color	Clear		
Texture	Glossy		
Non-Volatile	18 – 23% by volume		
Coverage (Theoretical)	50 - 55 sq.m./Gallon		
Wet Film Thickness	60 - 70 microns		
Dry Film Thickness	11 - 16 microns		
Application	Brush, Roller		
Diluent	Clean Water	5 - 10%	by volume
Drying Time (21-27°C and 50% RH)	Touch Dry	30 - 60	minutes
	Hard Dry	1 - 2	hours
	Re-Coat	6 - 12	hours

SURFACE PREPARATION

For re-painting, make sure the surface to be painted is free from dirt, grease, waxy contaminants, and loose, peeling paint. If mold and fungus appear on the painted surfaces, it is important that all existing mold be killed before applying a new coat of paint. One effective method for killing mold is to wash the mold-infested surfaces with Dyno Super Mold Killer. The treated surfaces are then rinsed with clean water and allowed to dry before repainting.

For new masonry surfaces, allow the surface to completely dry for a minimum of 30 days. Before painting, make sure the surface to be painted is free from dirt, grease, and waxy contaminants.

SUGGESTED COATING SYSTEMS

For Repainting On The Chalky Painted Surfaces

Dyno Chalking Sealer Water-based P-1200	1 Coat
Dyno Acrylic Emulsion/Dynopro/Dynolux/Dynosilk	2 Coats