

# ATF CVT

## **Description & Applications**

High performance transmission oil for use in the CVT gearbox of passenger cars.

#### Features

Provides effective power and protecting in the system.

# **Performance Specifications**

DEX-CVT



## **Typical Properties**

Density, 1 <mark>5°C, kg/L</mark>	ASTM D4052	0.86
K.Viscosit <mark>y, 40°C, mm²/s</mark>	ASTM D445	min.30
K.Viscosity <mark>, 100°C, mm²/s</mark>	ASTM D445	7.3
Viscosity Ind <mark>ex</mark>	ASTM D2270	min.120
Flash Point, °C	ASTM D92	min.200

### Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

ATF CVT AUTOMATIC TRANSMISSION

April 2023

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either G-Sol or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.





 $\bigcirc$