



15W-40 CK-4

ACEA E6/E9/E7 ACEA E8/E11

Description & Applications

Fully synthetic premium engine oil for naturally aspirated and turbocharged four-stroke diesel and gasoline engines operating under severe service in a wide range of climatic conditions, delivering API CK-4 performance.

Features

URSATECH 15W40 CK-4 is fully backwards compatible with API CJ-4 and API CI-4 and is designed to meet key European specification requirements for new engine hardware and operating conditions.

Performance Specifications

SAE 15W40 API CK-4 CJ-4/SN
ACEA E6/E9/E7 ACEA E8/E11
MB 228.31 MB 228.52 VOLVO VDS-4 VDS-4.5
RN VI RLD-3
MAN M 3275 MAN M 3775
MACK EOS-4.5 FORD WSS-M2C171-F



Typical Properties

Density, 15°C, kg/L	ASTM D4052	0.88
K.Viscosity, 40°C, mm²/s	ASTM D445	107.5
K.Viscosity, 100°C, mm²/s	ASTM D445	14.9
Viscosity Index	ASTM D2270	144
Flash Point, °C	ASTM D92	210
TBN, mgKOH/g	ASTM D2896	9.8

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

15W-40 CK-4 ACEA E6/E9/E7 ACEA E8/E11
URSATECH

MAY 2023

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either G-Sol or its subsidiaries for any damage or injury resulting from



URSATECH

+49-151-59070391



Info@gsol.ch



Ludwig-Erhard-Straße 14
65760 Eschborn, Germany

