



# 10W-40 UHPD LOW SAPS

## Description & Applications

High performance motor oil for commercial vehicles based on the so called 'low SAPS' technology. This means that sulphur, phosphorus and sulphated ash concentrations are reduced radically, to protect the exhaust gas after treatment systems.

## Features

URSTATECH 10W40 UHPD is a specially MB (228.51) and MAN (M3477) have set up special standards for the oil to meet Euro-4 and Euro-5 emission regulations, including reduced sulphur, phosphorus and sulphated ash concentrations.

## Performance Specifications

SAE 10W40 UHPD API CI-4/SN  
ACEA E6/E9 E7 ACEA E8/E11  
MB 228.51 MB 226.9 VOLVO VDS-3 RN VI RLD-2  
MAN M 3477 MAN M 3271-1  
DAF IVECO 18-1804 TLS E6  
RN RXD RN RGD MACK EO-N  
SCANIA LOW ASH



## Typical Properties

Density, 15°C, kg/L	ASTM D4052	0.864
K.Viscosity, 40°C, mm²/s	ASTM D445	98.1
K.Viscosity, 100°C, mm²/s	ASTM D445	14.7
Viscosity Index	ASTM D2270	156
Flash Point, °C	ASTM D92	232
TBN, mgKOH/g	ASTM D2896	10.01

## Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

10W-40 UHPD LOW SAPS  
URSTATECH

MAY 2023

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either G-Sol or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.



URSTATECH

+49-151-59070391



Info@gsol.ch



Ludwig-Erhard-Straße 14  
65760 Eschborn, Germany

