

5W-30 ACEA A3/B4

FULL SYNTETIC OIL

Description & Applications

Synthetic engine oil providing maximum performance in gasoline or diesel vehicles.

Features

Provides high protection and lubricating.

Performance Specifications

SAE 5W-30 API SN ACEA A3/B4 MB 229.3 VW 502/505 PORSCHE A40





Typical Properties

Density, 1 <mark>5°C, kg/L</mark>	ASTM D4052	0.86
K.Viscosit <mark>y, 40°C, mm²/s</mark>	ASTM D445	min.30
K.Viscosity <mark>, 100°C, mm²/s</mark>	ASTM D445	10.7
Viscosity Index	ASTM D2270	151
Flash Point, °C	ASTM D92	min.200
TBN, mgKOH/g	ASTM D2896	min.3

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

5W-30 ACEA A3/B4 ULTRATECH

April 2023

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility to the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either G-Sol or its subsidiaries for any damage or injury resulting from abarromal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Info@gsol.ch (💌)

+49-151-59070391 (



