


Black Jade-Flow

DOUBLE-TRANSPARENT GLASS BIFACIAL N-TYPE MODULE

490~505 W



Cutting Free Technology
Minimized micro-crack



Bifacial Mono Module
Capable of generating power at back side, at least 80% efficiency of the front side




Anti-PID (potential induced degradation)
Passed anti-PID test under 85°C damp heat 85% relative humidity for 192 hours



Lower LCOE
Lower shading and resistive loss
Lower temperature coefficient



Outstanding mechanical load resistance
2400 Pa wind load, 5400 Pa snow load



25-year product warranty
30-year linear power output
DEMAT-250515



CEC Listed



IEC 61215, IEC 61730

ISO 9001: 2015 (Quality management systems)

ISO 14001: 2015 (Environmental management systems)

ISO 45001: 2018 (Occupational health and safety)

UNI 9177 la CLASSE DI REAZIONE AL FUOCO:1

Add: No. 238 Yunlin Middle Road, Wangchun Industrial District, Ningbo China

Tel: +86-574-28828939

Email: sales@ulsolar.com.cn

Fax: +86-574-28828997

Web: www.ulicasolar.com



TOPCon(N TYPE)490~505Watt

ELECTRICAL SPECIFICATIONS

Module Type	UL-490M-120BDGN			UL-495M-120BDGN		UL-500M-120BDGN		UL-505M-120BDGN	
	STC*		NOCT*	STC*		NOCT*	STC*		NOCT*
Maximum Power (Pmax)	W	490	371	495	375	500	379	505	383
Maximum Power Voltage (Vmp)	V	36.68	33.75	36.85	33.90	37.02	34.06	37.18	34.21
Maximum Power Current (Imp)	A	13.36	11.00	13.43	11.06	13.51	11.13	13.58	11.19
Open-circuit Voltage (Voc)	V	43.35	39.45	43.52	39.60	43.78	39.84	43.98	40.02
Short-circuit Current (Isc)	A	14.35	11.58	14.43	11.64	14.48	11.68	14.54	11.73
Module Efficiency STC	%	22.14		22.36		22.59		22.81	
Operating Temperature				-40°C~85°C					
Maximum system voltage				DC1500V(IEC)					
Maximum series fuse rating				30A					
Power tolerance				0~+5 Watt					
Temperature coefficients of Pmax				-0.29%/°C					
Temperature coefficients of Voc				-0.25%/°C					
Temperature coefficients of Isc				0.046%/°C					
Nominal operating cell temperature (NOCT)				43±2°C					

*STC : Cell temperature: 25°C, Irradiance: 1000 W/m², Air mass: 1.5G

*NOCT : Air temperature: 20°C, Irradiance: 800 W/m², Air mass: 1.5G, Wind speed: 1 m/s

SPECIFICATIONS



Cell Type	N type Mono-crystalline	
No. of cells	120(6×10×2)	
Dimensions	1952*1134*30mm	
Weight	26.5kg	
Front Glass	2.0mm+2.0mm, Anti-Reflection Coating, High Transmission, Low Iron, Tempered Glass	
Junction Box	IP68, 3 diodes	
Connector	MC4 Compatible	
Cable Length (Including Connector)	4mm² Landscape: (+)1200mm/(-)1200mm or Customized Length	
Packaging Configuration	Two Box=One Pallet 36pcs/Box, 72pcs/Pallet, 864pcs/40HQ Container	

Electrical characteristics with different rear side power gain(reference to 500 W front)



Pmax/W	Voc/V	Isc/A	Vmp/V	Imp/A	Pmax gain
500	43.78	14.48	37.02	13.51	0%
525	43.78	15.20	37.02	14.18	5%
550	43.78	15.93	37.02	14.86	10%
575	43.78	16.65	37.02	15.53	15%
600	43.78	17.38	37.02	16.21	20%
625	43.78	18.10	37.02	16.88	25%
650	43.78	18.82	37.02	17.56	30%

I-V CURVE

I-V characteristics at different irradiances (reference to 500 W)



I-V characteristics at different temperature



Specifications included in this datasheet are subject to change without notice.

Ulica Solar reserves the right of final interpretation.

Version No.: UL-1952-120BDGNTHC-30-EN-V1.1