

black sprint

Product data sheet no. 9114 - R-05

Issue: June 2025

Directly in the moments beforehand all expectations are directed towards it: **SPORTEC® black sprint**. This elastic sub-base offers toughness and reliability for run-up or warm-up tracks in track and field athletics, in street ball and other multipurpose outdoor areas. **SPORTEC® black sprint** proves itself through cost-effective and rapid installation – fixed on firmly compacted sub-structure. The surface coatings offered, made of polyurethane with EPDM granules, make **SPORTEC® black sprint** resistant to loads such as spikes, UV light and extreme weather conditions. A special reinforcing layer guarantees stability of shape and stabilises movements of both track and field athletes and sport enthusiasts over a long period of time. **SPORTEC® black sprint** is resistant to decay, does not harden and does not embrittle.

Material

Material:

A mixture of black recycling rubber granules bonded with polyurethane elastomer.

Product design

Colour(s): black

Colour(s):



SPORTEC black sprint

Surface: granule structure

Dimensions / Tolerances / Weight

Thickness(es): 10 mm* (± 0.3 mm)

The product data sheet is not subject to any change service! All information is without guarantee.

Latest version of this document available on www.kraiburg-relastec.com/sportec

page 1 of 2

black sprint**Product data sheet no. 9114 - R-05**

Issue: June 2025

Roll width:	1,250 mm ($\pm 1.5 \%$)
Roll length:	36 m* (at 10 mm) ($\pm 1.5 \%$) (* other thicknesses and lengths on request)
Density:	approx. 650 kg/m ³
Area weight:	approx. 6.5 kg/m ² (at 10 mm)

Product Testing

Tensile strength:	min. 0.2 N/mm ² (EN ISO 1798)
Elongation at break:	min. 35 % (EN ISO 1798)
Water permeability:	4,500 cm/h (EN 12616)
Force reduction:	approx. 33.7% (at 10mm) (internal tested)
VOC emission rating:	French VOC Regulation (A+) French CMR components Italian CAM Edilizia ABG/AgBB Belgian Regulation Indoor Air Comfort Indoor Air Comfort Gold Formaldehyde Emission Class\$ (E1) Blue Angel (DE-UZ 120) BREEAM International (Exemplary Level) BREEAM-NOR (Exemplary Level) EU Taxonomy LEED v4.1 BETA (outside U.S.)

tested according to eurofins Indoor Air Comfort® Gold

Installation

Installation has to be done in accordance to the Installation Recommendation of **SPORTEC® black sprint**. The latest version of the Installation Recommendation can be downloaded at the website of KRAIBURG Relastec GmbH & Co. KG.

The product data sheet is not subject to any change service! All information is without guarantee.

Latest version of this document available on www.kraiburg-relastec.com/sportec

page 2 of 2