

**1. Applications**

EUROFLEX® Law Edging are used besides playgrounds and sports facilities excels in numerous other applications including edge trim for walkways, sidewalks, edge trim for trees and bushes, enclosures around and between laws or for beach volleyball areas.

EUROFLEX® Law Edging is made from selected recycled rubber material which is highly flexible (90°), Easy to cut, highly resistant to outdoor weathering and provides maximum protection against injuries.

**2. Material**

Rubber granulate: granulated recycled rubber  
Binding agent: MDI polyurethane

**3. Characteristics**

Colour: Reddish brown, green, grey or black  
(minor colour variation possible)  
Surface: smooth with open pores  
One side has anchoring grooves near lower edge  
Two connector pins for connection to adjacent elements

**4. Dimensions / Tolerances**

L x W x T: 1000 x 250 x 50 mm  
Tolerances: length, width: +/- 0,8 %, thickness: +/- 2 mm  
Weight: approx. 11,0 kg


**5. Material Lawn Edging with EPDM border**

Rubber granulate: granulated recycled rubber  
Border: colored new EPDM granulate  
Binding agent: MDI polyurethane

**6. Characteristics**

Colour lower part: red  
Colour view edge:

**ATTENTION: the color specification base on RAL and may differ from the product.**



**Standard SBR Lawn Edging and with EPDM border**Data sheet No. 9343- R -10  
Edition: November 2024**EPDM  
standard colours****EPDM  
special colours**

(minor colour variation possible)

Surface: smooth with open pores  
One side has anchoring grooves near lower edge  
Two connector pins for connection to adjacent elements

All information without guarantee, subject to change. The Data Sheet is not subject to any change service.  
Each current and valid from can be recalled at [www.kraiburg-relastec.com/euroflex](http://www.kraiburg-relastec.com/euroflex)

page 2 of 3

**7. Dimensions / Tolerances**

L x W x T: 1000 x 250 x 50 mm  
Tolerances: length, width: +/- 0,8 %, thickness: +/- 2 mm  
Weight: approx. 11,0 kg

**8. Test Data**

Conformity acc. to Regulation (EC) 1907/2006 SVHC list and appendix XVII

Production facility inspection

**9. Installation**

Insert EUROFLEX® Lawn Edging elements in prepared fresh concrete bed (grade: B15), forming concrete to a slope 10 cm high on both sides of the edging elements.

Be certain that the concrete covers the anchoring grooves.

Apply 1-component PU adhesive cement on mating surfaces of elements to be connected.

Join the elements using the connector pins supplied.

Note the complete installation instruction.

All information without guarantee, subject to change. The Data Sheet is not subject to any change service.  
Each current and valid from can be recalled at [www.kraiburg-relastec.com/euroflex](http://www.kraiburg-relastec.com/euroflex)

page 3 of 3