

DOL 139 3-in-1 sensor

Monitor temperature, humidity, and CO2 with one sensor.

Save time and money using the DOL 139

Since DOL 139 measures both humidity, temperature, and CO2, it makes an easier installation and maintenance as well as a cheaper solution, as the need for two or three different sensors is avoided.

A strong sensor with a long lifetime

The sensor is specially designed to withstand the harsh conditions in livestock houses and industrial environments.

Withstands high-pressure cleaning

DOL 139 is protected by a sturdy casing and behind a carefully selected filter and is supplied with a protection cap for protection of the sensor during washing and disinfection even during high-pressure cleaning.

Easy replacement

It is easy to replace DOL 19 or DOL 119 CO2 sensors as well as DOL 104 humidity sensor and DOL 114 humidity and temperature sensor with a DOL 139, which will then serve as the only sensor needed for measuring humidity, temperature, and CO2.

Benefits

- Avoid CO2 accumulation
- No more removing or destruction of sensors during high-pressure cleaning
- Improve animal welfare
- Avoid higher FCR
- Avoid higher mortality
- Collect data for management purpose

Advantages

- Easily replacement of DOL 19, DOL 119, DOL 114, and DOL 104
- Reliable and accurate monitoring of the CO2 level, humidity and temperature
- Easy mounted protection cap

