

Product

Catalog No.

Fixture Type

Notes



RH772 LED Round High Bay Light

RH772 Round High Bay Light is a cost-effective and compact high bay light, available in three power options—100W, 150W, and 200W—across three different sizes to optimize cost and freight efficiency. Featuring a dotted lens design with UGR<24, it ensures comfortable, glare-reduced illumination. The luminaire offers flexibility with optional 1 PIN or 3 PIN sockets, while its Twist Central Intelligent Control system provides an adaptable solution for both wholesale and contract channels.

APPLICATIONS

- Warehouse
- Distribution Center
- Manufacturing Plant
- Gymnasium
- Shopping Malls
- Convention Center
- Exhibition Halll
- Auditorium

FEATURES

- Low UGR, confortable for eyes
- Excellent lumen efficacy: ~165 lm/W
- 0-10V dimming standard
- IP66 and IK08 double protection, with super reliability.
- Wattage tunable

Unit: mm Onder 1 188 Assert 100W 150W 200W

SPECIFICATION SUMMARY

Category	Specification	Data	
Category Performance		60/80/100W (Selectable);	
	Wattage	90/120/150W (Selectable);	
		120/160/200W (Selectable)	
	Delivered Lumens	16,500 lm; 24750 lm; 33,000 lm	
	Lumen Efficacy	~165 lm/W	
	Lens Option	Polycarbonate Optical Lens	
	Color Temperature	5000K (3000K, 4000K optional)	
	CRI (Ra)	>80	
	Beam Angle	60°, 85°, 120°	
Electrical	Input Voltage	120-277V	
	Power Factor	>0.92	
	Surge Protection	6kV line-line, 6kV line-earth	
	Dimming	0-10V	
Physical	Housing	Aluminum Alloy	
	Operation Temperature	-22 to +122°F	
		100W: 9.76×6.1"	
	Dimension	150W: 10.47×6.38"	
		200W: 11.81×6.57"	
		100W: 4.41 lb	
	Weight	150W: 5.29 lb	
		200W: 5.95 lb	
	IP	IP65	
	IK Rating	IK08	
	Mounting Options	Chain / Surface	

LIFESPAN AND WARRANTY

Rated Life	50,000 Hrs
Warranty	5 Years
Certification	ETL

CERTIFICATION












PHOTOMETRY


100W Beam Angle










150W Beam Angle









200W Beam Angle







MOUNTING OPTIONS





Chain Mount

Surface Mount

ACCESSORIES









PC reflectors

Aluminum reflectors

Safety Chain

Motion Sensor









RIP Sensor

Remote Controller

Microwave Motion Sensor

RIP Sensor







Remote Controller

Ceiling Bracket

± 30° Adjustable Bracket

$\pmb{RH772} \; \text{LED Round High Bay Light}$

ORDERING INFORMATION

RH772

Series SKU	Wattage	CRI	Input Voltage	сст	Lens	Mounting (Optional)
RH772	100: 100/80/60W 150: 150/120/90W 200: 200/160/120W	L: 70 M : 80	U : 120-277V	30 : 3000K 40 : 4000K 50 : 5000K	C: Clear F: Frost	C : Chain S : Surface

Example: RH772-100MU-50CS

Lead times will vary depending on options selected.

Consult with your sales representative.

MISCELLANEOUS

CONSTRUCTION:
INSTALLATION:
OPTICS:
LISTINGS:
ELECTRICAL:
GOVERNMENT PROCUREMENT:

NOTE