

Product	
Catalog No.	
Fixture Type	Notes



WP2001 LED ROUND HIGH BAY LIGHT

WP2001 is a full cut-off LED wall pack built for outdoor architectural, commercial, and industrial environments. Featuring IP65 protection, durable die-cast aluminum housing, and optional sensors (photocell, microwave motion), it offers flexible wattage and CCT options. With high efficacy up to 130 lm/W and multiple Type II/III/IV distributions, WP2001 delivers performance, energy efficiency, and long life with plug-and-play installation


APPLICATIONS

- Building facades
- Commercial buildings
- Industrial parks
- Retail stores
- Hospitality facilities
- Warehouses
- Exterior perimeter walls



FEATURES

- IP65 rated for wet locations
- Photocell & motion sensor options
- UV-resistant lens
- DIP switch configurable


DIMENSIONS



30-60W(120-277VAC&120-347VAC) / 80W(120-277VAC)



80W(120-347VAC) / 100-120W(120-277VAC&120-347VAC)



SPECIFICATION SUMMARY

Category	Specification	Data
Category Performance	Wattage	30W, 40W, 50W, 60W, 80W, 100W, 120W
	Delivered Lumens	3,900 - 15,600 lm
	Lumen Efficacy	130 lm/W
	Color Temperature	3000K / 4000K / 5000K / 5700K
	CRI (Ra)	>70
	Beam Angle	117°
Electrical	Input Voltage	120-277VAC / 120-347VAC
	Dimming	0-10V
	Power Factor	>0.9
Physical	Housing	Die-cast aluminum
	Operation Temperature	-22°F to +113°F
	Dimension	30-60W: 8.7" × 9.1" × 6.7"
		80W: 9.2" × 11.05" × 7.2"
		100-120W: 9.2" × 11.05" × 7.2"
	Mounting Options	Wall
	IP Rating	IP65
	IK Rating	L-N: 2KV L/N-PE: 4KV

LIFESPAN AND WARRANTY

Rated Life	50,000 Hrs
Warranty	5 Years
Certification	ETL, DLC Premium

CERTIFICATION



WP2001 LED ROUND HIGH BAY LIGHT

PERFORMANCE DATA

PRODUCT CODE	WATTS	lm/W	DELIVERED LUMENS	Input Voltage	CRI (Ra)	CCT
WP2001	30W	130	3,900	AC120-277V / AC 120-347V	70	3000/4000/5000/5700K (Selectable)
WP2001	40W	130	5,200	AC120-277V / AC 120-347V	70	3000/4000/5000/5700K (Selectable)
WP2001	60W	130	6,500	AC120-277V / AC 120-347V	70	3000/4000/5000/5700K (Selectable)
WP2001	60W	130	7,800	AC120-277V / AC 120-347V	70	3000/4000/5000/5700K (Selectable)
WP2001	80W	130	10,400	AC120-277V / AC 120-347V	70	3000/4000/5000/5700K (Selectable)
WP2001	100W	130	13,000	AC120-277V / AC 120-347V	70	3000/4000/5000/5700K (Selectable)
WP2001	120W	130	15,600	AC120-277V / AC 120-347V	70	3000/4000/5000/5700K (Selectable)

ORDERING INFORMATION

WP2001					
Series SKU	Wattage	Input Voltage	CCT	Housing	Option (Optional)
WP2001	030: 30W 040: 40W 060: 60W 080: 80W 100: 100W 120: 120W	U: 120-277V H: 120-347V	CT: CCT Selectable (30/40/50/57K)	D: Dark Bronze B: Black C: Customized	MS: Motion Sensor PC: Photocell

Example: WP1315-026UCTDPC
Lead times will vary depending on options selected.
Consult with your sales representative.

MISCELLANEOUS

NOTE

CONSTRUCTION:
INSTALLATION:
OPTICS:
LISTINGS:
ELECTRICAL:
GOVERNMENT PROCUREMENT: