

Product	
Catalog No.	
Fixture Type	Notes



DL808 DOWN LIGHT

The DL808 Saturn IP65 Series LED Downlight is a versatile recessed luminaire suitable for indoor and semi-outdoor applications such as bathrooms, corridors, and eaves. With wattages from 12W to 40W, it provides efficient illumination with CRI90 as standard (optional CRI97). Featuring a reflective cup structure, beam angle of 60°, and multiple dimming options (On/Off, Triac, 0-10V, DALI), the DL808 ensures high visual comfort (UGR<19). Available in round and square models, it is ETL certified and backed by a 5-year warranty.

APPLICATIONS

- Outdoor Patios and Decks
- Bathrooms and Shower Areas
- Parking Garages
- Poolside and Spa Areas
- Building Entrances and Canopies

FEATURES

- Reflective cup design
- Round & square options
- On/Off/Triac/0-10V/DALI dimming
- CRI90 standard (CRI97 optional)
- UGR<19

SPECIFICATION SUMMARY

Category	Specification	Data
Category Performance	Wattage	12W / 15W / 20W / 30W / 40W
	Delivered Lumens	1,080~3,600lm
	Lumen Efficacy	90 lm/W
	Color Temperature	2700/3000/4000/5000/6000K (Selectable)
	CRI (Ra)	90+
Electrical	Input Voltage	AC100-277V
	Dimming	On/Off, Triac, 0-10V, DALI
Physical	Housing	AL
	Beam Angle	60°
	IP Rating	IP65
	Mounting Options	Recessed
	Dimensions (Cutout)	
	Round Models	12W: Ø4.38" × H2.50" (Ø4.00") 15W: Ø5.38" × H2.63" (Ø4.88") 20W: Ø6.88" × H3.38" (Ø6.25") 30W: Ø7.50" × H3.88" (Ø6.75") 40W: Ø9.00" × H4.38" (Ø8.13")
	Square Models	12W / 15W: 4.38" × 4.38" × H2.38" (4.38" × 4.38") 20W: 5.00" × 5.00" × H3.00" (5.00" × 5.00") 30W: 6.50" × 6.50" × H3.00" (5.75" × 5.75") 40W: 8.25" × 8.25" × H3.00" (7.50" × 7.50")

LIFESPAN AND WARRANTY

Rated Life	50,000 Hrs
Warranty	5 Years
Certification	ETL


CERTIFICATION




DL808 DOWN LIGHT

DIMENSIONS

Round



Square



PERFORMANCE DATA

PRODUCT CODE	TYPE	SIZE	WATTS	DELIVERED LUMENS	INPUT VOLTAGE	CCT
DL808	Round	4.00"	12	1,080	AC100-277V	2700/3000/4000/5000/6000K (Selectable)
		4.88"	15	1,350		
		6.25"	20	1,800		
		6.75"	30	2,700		
		8.13"	40	3,600		

PRODUCT CODE	TYPE	SIZE	WATTS	DELIVERED LUMENS	INPUT VOLTAGE	CCT
DL808	Square	4.38" x 4.38"	12	1,080	AC100-277V	2700/3000/4000/5000/6000K (Selectable)
		4.38" x 4.38"	15	1,350		
		5.00" x 5.00"	20	1,800		
		5.75" x 5.75"	30	2,700		
		7.50" x 7.50"	40	3,600		

DL808 DOWN LIGHT

ORDERING INFORMATION

DL808					
Series SKU	Wattage	Dimming	Voltage	CCT	Type
DL808	012: 12W 015: 12W 020: 20W 030: 30W 040: 40W	DO: On-off DT: Triac DV: 0-10V DD: Dali *Leave blank if not specified	U: 100-277V	CT: CCT Selectable (2700/3000/4000/ 5000/6000K)	R: Round S: Square

Example: DL808-040DVU-CTR
Lead times will vary depending on options selected.
Consult with your sales representative.

MISCELLANEOUS

CONSTRUCTION:
INSTALLATION:
OPTICS:
LISTINGS:
ELECTRICAL:
GOVERNMENT PROCUREMENT:

NOTE