

Product	
Catalog No.	
Fixture Type	Notes



LS246 LED LINEAR LIGHT

The LS246 LED Slim Wrap Light features a clean, low-profile curved design that delivers uniform illumination with high efficiency. Built with a heavy-gauge steel housing and a high-transmittance polycarbonate lens, it provides excellent durability and glare-controlled light distribution. With selectable CCT options and long LED lifetime, the LS246 is an ideal solution for commercial and institutional lighting applications requiring reliable, energy-efficient performance.


APPLICATIONS

- Storage Rooms
- Offices
- Conference Rooms
- Retail
- Reception Areas
- Hallways
- Education Facilities

FEATURES

- Heavy Gauge Steel Housing
- Wiring knockouts are provided on back and end of housing
- Fast and easy to install
- Quick disconnects between housing
- Driver disconnect provided where required to comply

DIMENSIONS



SPECIFICATION SUMMARY

Category	Specification	Data
Category Performance	Wattage	2' : 20W 4' : 40W
	Delivered Lumens	2,400 - 4,800lm
	Lumen Efficacy	120lm/W
	Color Temperature	3500/4000/5000K(Selectable)
	CRI (Ra)	82
Electrical	Input Voltage	AC120-277V
	Dimming	0-10V
	Power Factor	0.98
Physical	Housing	Aluminum
	Beam Angle	90°
	Operation Temperature	-22°F to 104°F
	IP Rating	IP20
	Mounting Options	Surface / Suspended
	Dimensions	48(24)\"x4.57\"x2.6\"

LIFESPAN AND WARRANTY

Rated Life	50,000 Hrs
Warranty	5 Years
Certification	UL

CERTIFICATION



LS246 LED STAIRWELL LIGHT

PERFORMANCE DATA

2'	PRODUCT CODE	WATTS	lm/W	DELIVERED LUMENS	Input Voltage	CRI (Ra)	CCT
	LS246-02	20	120	2,400	AC120-277V	82	3500/4000/5000K(Selectable)

4'	PRODUCT CODE	WATTS	lm/W	DELIVERED LUMENS	Input Voltage	CRI (Ra)	CCT
	LS246-04	40	120	4,800	AC120-277V	82	3500/4000/5000K(Selectable)

MOUNTING OPTIONS



Surface Mount



Chain Mount

Accessories



Emergency Backup Battery



Occupancy Motion Sensor

LS246 LED STAIRWELL LIGHT

ORDERING INFORMATION

Series SKU	Size	Wattage	Dimming	Voltage	CCT	Mounting	Accessories (Optional)
LS246	02: 2ft ----- 04: 4ft	020: 20W ----- 040: 40W	DV: 0-10V Dim *Leave blank if not specified	U: 120-277V H: 120-347V	CT: CCT Selectable 3500/4000/5000K	SM: Surface Mount CM: Chain Mount	EM: Emergency Battery OS: Occupancy Sensor

Example: LS246-04040DVU-CTCM
 Lead times will vary depending on options selected.
 Consult with your sales representative.

MISCELLANEOUS

CONSTRUCTION:
 INSTALLATION:
 OPTICS:
 LISTINGS:
 ELECTRICAL:
 GOVERNMENT PROCUREMENT:

NOTE