

Product	
Catalog No.	
Fixture Type	Notes



TD401 TEARDROP CLEANROOM LUMINAIRE

TD401 is a 2-inch wide teardrop cleanroom luminaire designed for high-efficiency lighting in controlled environments. Featuring a sleek antimicrobial finish, dimmable LED driver, and multiple lumen options up to 8,000 lm, it supports universal voltage (120-277V) and offers high efficacy up to 155 lm/W. Ideal for cleanrooms, labs, and healthcare facilities.


APPLICATIONS

- Clean Room
- Hospital
- Laboratory
- Retail
- Reception areas
- Hallways
- Industrial Facilities

FEATURES

- Can be mounted directly to T-bar grid
- 2" wide teardrop cleanroom design
- Suitable for ISO Class 5 / Class 100 cleanrooms
- High efficacy up to 149 lm/W
- 0-10V dimming driver standard

DIMENSIONS



SPECIFICATION SUMMARY

Category	Specification	Data
Category Performance	Wattage	12 ~ 70W (Optional)
	Delivered Lumens	2,000 ~ 10,000lm
	Lumen Efficacy	126 ~ 149lm/W
	Color Temperature	2700/3000/3500/4000/5000K (Optional)
	CRI (Ra)	80+
Electrical	Input Voltage	AC120-277V
	Dimming	0-10V Standard
	Power Factor	0.9
Physical	Housing	Aluminum
	Beam Angle	90°
	Operation Temperature	-4°F to 95°F
	Mounting Options	Ceiling
	Dimensions	48(24)"x2"x5"

LIFESPAN AND WARRANTY

Rated Life	50,000 Hrs
Warranty	5 Years
Certification	UL


CERTIFICATION



TD401 TEARDROP CLEANROOM LUMINAIRE

PHOTOMETRY

TD401-04025DVUF50



Distribution Curve

C-plane — C0/180 — C90/270

Category	Details (C0°)
Luminous Flux	4,185 lumens
Luminous Efficacy	87.2%
Power Consumption	26W
Peak Intensity	906.3 cd
Light Distribution	Symmetrical, Wide beam
Beam Spread Pattern	Oval-shaped, uniform diffusion
CCT (Color Temp.)	4,000K
Recommended Height	8–12 ft

PERFORMANCE DATA

2'	PRODUCT CODE	WATTS	lm/W	DELIVERED LUMENS	INPUT VOLTAGE	CRI (Ra)	CCT
	TD401-02	27	131.1	4,000	AC120-277V	80+	2700/3000/3500/4000/5000K (Optional)
	TD401-02	35	126.0	5,000	AC120-277V	80+	2700/3000/3500/4000/5000K (Optional)

4'	PRODUCT CODE	WATTS	lm/W	DELIVERED LUMENS	INPUT VOLTAGE	CRI (Ra)	CCT
	TD401-04	12	149.2	2,000	AC120-277V	80+	2700/3000/3500/4000/5000K (Optional)
	TD401-04	20	142.6	3,000	AC120-277V	80+	2700/3000/3500/4000/5000K (Optional)
	TD401-04	25	142.6	4,000	AC120-277V	80+	2700/3000/3500/4000/5000K (Optional)
	TD401-04	40	137.7	6,000	AC120-277V	80+	2700/3000/3500/4000/5000K (Optional)
	TD401-04	53	133.4	8,000	AC120-277V	80+	2700/3000/3500/4000/5000K (Optional)
	TD401-04	70	128.2	10,000	AC120-277V	80+	2700/3000/3500/4000/5000K (Optional)

TD401 TEARDROP CLEANROOM LUMINAIRE

MOUNTING OPTIONS



Surface Mount

Accessories



Emergency Backup Battery



Occupancy Motion Sensor

ORDERING INFORMATION

Series SKU	Size	Wattage	Dimming	Voltage	Lens	CCT	Mounting (Optional)	Accessories (Optional)
TD401	02: 2ft ----- 04: 4ft	027: 27W 035: 35W 012: 12W 020: 20W 025: 25W 040: 40W 053: 53W 070: 70W	DV: 0-10V Dim *Leave blank if not specified	U: 120-277V	F: Frosted A: Amber	27: 2,700K 30: 3,000K 35: 3,500K 40: 4,000K 50: 5,000K	CM: Chain CL: Ceiling	EM: Emergency Battery OS: Occupancy Sensor

Example: TD401-04025DVUF-50CL
Lead times will vary depending on options selected.
Consult with your sales representative.

MISCELLANEOUS

CONSTRUCTION:
INSTALLATION:
OPTICS:
LISTINGS:
ELECTRICAL:
GOVERNMENT PROCUREMENT:

NOTE