

Product	
Catalog No.	
Fixture Type	Notes



## SPECIFICATION SUMMARY

Category	Specification	Data
Category Performance	Wattage	9": 80/60/50/40W (Selectable)
		9": 120/100/80/60W (Selectable)
	Delivered Lumens	-18,000lm
	Lumen Efficacy	-150lm/W
	Color Temperature	3000K / 4000K / 5000K (Selectable)
Electrical	CRI (Ra)	80+
	Input Voltage	120-277V / 120-347V
	Dimming	0-10V
Physical	Power Factor	≥ 0.9
	Housing	Die-cast aluminum housing
	Operation Temperature	-40°F to +113°F
	IP Rating	IP 65
	Mounting Options	Wall Mount
	Dimension	8" : 10.1" × 9.4" × 6.3"

## WP2032 LED WALL PACK

The WP2032 LED Rotating Wall Pack is a high-performance, adjustable outdoor wall-mounted lighting solution designed for precise area illumination. Featuring a tool-less rotating head with a wide adjustment range, selectable wattage and CCT, and integrated photocell control, WP2032 easily adapts to different site requirements. Its durable die-cast aluminum housing and IP65 rating ensure long-term reliability in demanding outdoor environments, delivering energy-efficient, long-lasting illumination for commercial and residential applications.

### APPLICATIONS

- Walkways & pathways
- Parking areas
- Landscape lighting
- Outdoor commercial buildings
- Outdoor residential areas

### FEATURES

- High efficacy up to 150 lm/W
- 3 CCT selectable: 3000K / 4000K / 5000K
- 4 wattage selectable for flexible output
- Tool-less rotating head adjustable from -15° to 210°
- Integrated photocell ON/OFF (dusk-to-dawn)


### LIFESPAN AND WARRANTY

Rated Life	50,000 Hrs
Warranty	5 Years
Certification	UL

### CERTIFICATION



### DIMENSION



# WP2032 LED WALL PACK

## PERFORMANCE DATA

PRODUCT CODE	SIZE	WATTS	DELIVERED LUMENS	VOLTAGE	DIM	CCT
WP2032	9"	80/60/50/40W (Selectable)	12000LM @80W	AC120-277V	0-10V	3000K, 4000K, 5000K (Selectable)
WP2032	9"	120/100/80/60W (Selectable)	18000LM @120W	AC120-347V		

- All above efficacy and lumens are subject to CRI>80 @4000K, please check IES files for accurate data.
- Factory default settings: Photocell is ON, Max wattage, 5000K.

## ACCESSORIES



Microwave motion sensor



Plug-in Microwave Motion Sensor



Emergency driver 8W

## ORDERING INFORMATION

Series SKU	Size	Wattage	Input Voltage	CCT	ACCESSORIES
WP2032	09: 9"	080: 80/60/50/40W (Selectable) 120: 120/100/80/60W (Selectable)	U: 120-277V H: 120-347V	CT: CCT Selectable (30K/40K/50K)	MS: Microwave Sensor BS: Bluetooth Microwave Sensor PS: Plug-in Microwave Motion Sensor PB: Plug-in Bluetooth Microwave Motion Sensor EM: Emergency driver

Example: WP2032-09080U-CTMS  
Lead times will vary depending on options selected.  
Consult with your sales representative.

## MISCELLANEOUS

CONSTRUCTION:  
INSTALLATION:  
OPTICS:  
LISTINGS:  
ELECTRICAL:  
GOVERNMENT PROCUREMENT:

## NOTE