




GENERAL INFORMATION

The THORNE G is a low-profile garden bollard designed for ambient pathway and landscape lighting, featuring a frosted acrylic diffuser that delivers soft, 360° Type V symmetrical illumination. With IP65 protection, multiple finish and CCT options, and integral 0-10V dimming, it offers both aesthetic refinement and reliable performance in outdoor environments.



SPECIFICATIONS

Material	Extruded Aluminum + PMMA
Lens	Frosted, Acrylic
Diameter	6" / Custom on request*
Total Height	14"
Base Height	8"
Light Source Type	LED
Power	9.5W / 17W
Input Voltage	110-277V, 50-60 Hz
LED Output	48 lm/W
CCT	2200K / 2700K / 3000K / 4000K / 5000K
CRI	90
Dimming & Driver	Integral, 0-10V
Light Distribution	Type V 360° symmetrical light distribution
IP Rating	IP 65
Warranty	5 years
Finishes	16 standard finishes 8 wood-effect finishes 12 metallic finishes Custom on request*

OTHER VERSIONS AVAILABLE



CERTIFICATION




Ordering Information

Select one item from each category below. If your desired option is unavailable, please contact our team for support or custom solutions.

Code	Diameter Ø	Height	Material
☒ THR-G Garden	☐ 6 6" ☐ Cus Custom on request	☐ 14 14" ☐ Cus Custom on request	☒ AL Extruded Aluminum
CCT	Wattage / Lumens	Light Distribution	Dimming
☐ 22 2200K ☐ 30 3000K ☐ 40 4000K ☐ 50 5000K	☐ 45 9,5 W / 450 lm ☐ 81 17 W / 815 lm ☐ Cus Custom on request	☒ LD5 Type V 360° symmetrical light distribution	☐ NN Non-Dimmable ☐ DM 0-10V
Body Finish Options	Base Finish Options	Mounting	
☐ ST Standard ☐ WE Wood effect ☐ MC Metallic ☐ Cus Custom on request	☐ ST Standard ☐ WE Wood effect ☐ MC Metallic ☐ Cus Custom on request	☒ SM Surface-mounted	

Finishes


Standard finishes



RAL K7 CLASSIC COLORS
(80-95% GLOSS): RAL_ _ _ _

All RAL Classic colors are available with no setup fee.


On your specification submittal, choose your RAL color by entering the 4-digit RAL code (e.g., RAL 3003).



Wood-effect finishes



Metallic finishes




Project

Notes

Bolt Patterns

for Surface-mounted Installation



Mounting Type	Surface-mounted
Base Plate Material	Stainless Steel
Bolt Mounting Circle	$\phi: 4-7/10''$
Number of Anchor Bolt	4 equally holes (90° apart)
Bolt Size	$1/4''-20 \times 3 \ 1/4''$ concrete anchor bolt

- Installation Notes:**
- Use a manufacturer-supplied base plate to position anchor bolts accurately.
 - Ensure bolts are embedded vertically and aligned to avoid fixture tilt.
 - Grouting under the base plate is recommended for leveling and load distribution.
 - Allow clearance for wiring through the center opening and access to bolt heads if concealed.